

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Grand Fir 11" dia., bears N.20°E., 44 lks. dist. with healed double blaze.

A Fir 6" dia., bears N.57°W., 50 lks. dist. with fragmentary scribe marks visible on opened blaze.

This point was not recorded, as far as can be determined it was not recognized as the corner by adjacent landowners, and is not utilized in this survey.

(Haines report appears to have been recorded as H-111 after BLM research of records. V.L.)

Adam DeGroot - For: Weyerhaeuser Co. - May 2020 - C.S. File 65/105-13

Found - A 2½" USBLM stainless steel post by Rogers in 1988, firmly set and projecting 6" above ground, with a ¾" brass cap properly marked per the record.

The 1988 accessories -

The root hole of a down 18" G.Fir bears record N.30°15'E., 18.5 ft (N.30°15'E., 28 lks)

A 16" D.Fir bears N.56°45'W., 16.4 ft w/healed blaze (N.56°45'W., 25 lks)

A 1/2" Iron pipe bears S.54°39'44"W., 1.00 ft (S.53°08'00"W., 0.015 chs)

New BTs- A 21" Cedar bears N.35°E., 52.3 ft scribed "¼S15 BT" on dbl blaze.

A 12" Maple bears N.76°30'E., 35.0 ft scribed "¼S15 BT" on dbl blaze

A 10" G.Fir bears N.77°30'W., 29.9 ft with healed single blaze - (BT previously marked for old corner locations)