

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1338)

Set post cor. of secs. 9, 10, 15 and 16, from which
A Fir 24" dia., bears S.28°W., 38 lks. dist.
A Fir 8" dia., bears N.78°W., 22 lks. dist.
A Fir 12" dia., bears N.60°E., 30 lks. dist.
A Fir 6" dia., bears S.18°E., 42 lks. dist.

Cor. Fd. and used in GL0 survey by Wm. P. Wright, under Contract #514, dated Aug. 27, 1884 (DCSO records, Vol. 4 Page 1360)

Douglas Co. Surveyors Office - James Byron, Deputy - M. Godfrey and S. Bilow, crew - May 12, 1958 - C.S. 49/59-25

Found - Orig. 8" now 26" Fir, N.78°W., 14.5 ft. I open and find good scribing "RS".
The orig. NE. and SE. BTs down and I find hole in ground for orig. SW. BT. All check for bearing and distance.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 4 W
S 9 | S 10
S 16 | S 15
1958

New BTs - Rescribed orig. N.78°W., 14.5 ft. BT, "S9 T22S R4W CS BT"
10" W. Fir S.36°W., 60.6 ft. scribed "S16 T22S R4W CS BT"
24" Cedar N.15°E., 68.3 ft. scribed S10 T22S R4W CS BT.
12" Yewwood, East 60.6 ft. scribed S15 T22S R4W CSBT

William L. Wilt - For: Weyerhaeuser Co. - Jan. 18, 1963 - C.S. File 53/105-9

GL0 survey record, 1855:
Post, no trace
24" Fir S.28°W., 38 lks.; stump hole only.
8" Fir N.78°W., 22 lks.; 26" Fir, old face chopped open, old scribing visible.
12" Fir N.60°E., 30 lks.; windfall, shows orig. scar.
6" Fir S.18°E., 42 lks.; windfall, shows orig. scar.
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Haines corner:

- Haines T Iron stake, good condition.
- 10" W.Fir S.36°W., 60.6 ft.; good condition.
- 24" I.Cedar N.15°E., 68.3 ft.; good condition.
- 12" Yew East, 60.6 ft.; good condition.

Found DCSO brass cap.

New Accessories added this date:

- 26" Fir N.78°W., 14.0 ft. (Orig. BT), "W" nail and plate.
- 24" I.Cedar N.15°E., 68.3 ft. (Haines BT) "W" nail & plate .
- 12" Yew N.89°E., 60.6 ft. (Haines BT) "W" nail & plate.
- 10" Fir S.35°W., 60.6 ft. (Haines BT) "W" nail & plate.

Fd. T-Iron & County cap, June 1975 by Haines (H. En. 7)
Cor. OK, Jan. 1965, B. Rogers, DCSO C.S. File 53/101-82

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1415, Surveyed Jan. 7/March 29, 1988 - (DCSO records Vol. 48 Page(s) 18625-26)

The Sec. Cor., perpetuated and recorded by Byron in 1958, monumented with an iron post 1¼" dia., firmly set, projecting 14" above ground with mkd. brass cap.,

from which the remains of original bearing trees:

- A root hole bears N.60°E., 30 lks. dist., with a down Fir stump alongside, size indeterminate, no marks visible.
- A root hole bears S.18°E., 42 lks. dist.
- A Fir 32" dia., bears N.78°W., 22 lks. dist., with healed face.

and the remains of bearing trees mkd. by Byron:

- A sawed Cedar stump 22" dia., bears N.15°E., 102 lks. dist. with scribe marks T22S R4W S10 CS BT visible on partially healed double blaze.
- A Grand Fir 23" dia., bears S.38°W., 92 lks. dist., with healed double blaze.

and new bearing trees:

- A Fir 11" dia., bears N.73½°E., 32½ lks. dist., mkd. T22S R4W S10 BT.
- A Fir 15" dia., bears S.60 ¾°E., 48½ lks. dist., mkd. T22S R4W S15 BT.

The corner is located South, 0.30 chs. dist. from creek, 3 lks. wide, course N.75°W.

continued next page

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group #1935, surveyed Jan./Feb. 2000 - (DCSO rec. Vol. 53 Page(s) 20374-5)

Beginning at the cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 1¼" diam., firmly set, projecting 16" above ground, (along the north side of which is a "T" post, 1 X 1", firmly set, projecting 14" above ground, with brass button, 1" diam., mkd. Haines Survey Point Drain OR 239), with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 22 S
S 9 | S 10
S 16 | S 15
R 4 W
1958

from which the remaining original bearing tree
A fir, 33" dia. bears N.78°W. 14.5 ft. with a healed blaze and the remains of bearing trees mkd. by Byron.
A sawed cedar stump, 18" diam., bears N.14¼°E., 67.5 ft., with scribe marks T22S R4W S10 CS visible on decayed face. (Record N.15°E., 67.3 ft.)
A fir, 25" diam., bears S.38°W., 60.7 ft., with a healed double blaze.
and bearing trees mkd. by Rogers and Moore.
A fir, 17" diam., bears N.72°E., 21.5 ft., with a healed blaze. (Record N.73½°E.)
A fir, 21" diam., bears S.60 3/4°E., 31.5 ft., with a healed blaze. (Record 32.0 ft.)

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO recs Vol. 55 Pg 21804)

The cor. of secs. 9, 10, 15, & 16, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground (alongside of which is an iron T-post, 1" sq., firmly set, projecting 14" above ground with brass disk mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE), with brass cap (properly) mkd. from which an original bearing tree

A fir, 38" dia., bears N.78°W., 14.5 ft., with a healed blaze.
and the remains of BTs mkd. by Byron, in 1958, reported by Skeesick and Browning
A decayed cedar snag, size indeterminate, bears N.14¼°E., 67.5 ft., no marks visible.
A fir, 26" dia., bears S.38°W., 60.7 ft., with a healed blaze.

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Rogers and Moore, reported by Skeesick and Browning

A root hole bears N.72°E., 21.5 ft., with fallen fir snag, 19" dia., lying alongside, no marks visible.

A fir, 27" dia., bears S.60¾°E., 31.5 ft., with a healed blaze.

and new bearing trees

A fir, 17" dia., bears N.21½°E., 59.0 ft., mkd. T22S R4W S10 BT.

A fir, 7" dia., bears S.21¾°W., 49.8 ft., mkd. X BT.

From the cor. N., 20 ft., a creek, 2 ft. wide, course N.75°W.

The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined in a least squares adjusted network of conventional survey control and GPS occupied points, utilizing dual frequency carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Stations (CORS) "DCS0 CORS ARP" and "OBEC CONS COOP CORS ARP", is as follows.

Latitude: 43°39'49.01"N. Longitude: 123°10'00.60"W.