

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1363)

Set post 4" dia., 4 ft. long, with marked stone 12" in the ground for qr. sec. cor., marked ¼ S on W. face, from which
A Fir 14" dia., bears N.60°E., 29 lks. dist. mkd. ¼ S BT.
A Fir 30" dia., bears N.44°W., 54 lks. dist. mkd. ¼ S BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1026, surveyed July 15, 1980/March 12, 1981 (DCSO records Vol. 44 Page(s) 16972)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S R 4 W
1/4
S 4 S 3
1980

from which
A Fir 10" dia., bears S.13°E., 18 lks. dist. mkd. ¼ S3 BT.
A Fir 12" dia., bears N.36°W., 33 lks. dist. mkd. ¼ S4 BT.

FD OK BLM Resurvey, by Dale B. Bedell, Surveyed under Group No. 1703. Surveyed Aug. 1993 thru May 1994. (D.C.S.O. records Vol. 52 Page(s) 19653)