

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; and 3 of T23-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by - James E. Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 6 Page(s) 2266 and Page 2269)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Fir 17" dia., bears S.21°W., 62 lks. dist. A Fir 18" dia., bears South, 110 lks. dist.</p>
<p>Survey by Wilford N. Haines - For: Whipple Mill - June 1961 -M 22-6 and M 39-53</p> <p>-----</p> <p>Found - 18" Fir now 40", South 110 lks. Scribed stake, in place. Set 1" x 1" x 36" T. Iron by stake.</p>
<p>Survey by Donald Peel - For: Weyerhaeuser Co. - July 1988 - M 106-59</p> <p>-----</p> <p>Found - 34" Fir, South 72.6 ft. Orig. BT, opened to visible scribing. Set 2" x 42" Iron pipe with brass cap mkd: "T22S R4W 1/4 S34 S3 T23S PLS 752 1988". Haines T bar bears N.8°28'10"W., 10.8 ft. New BT - 13" Fir N.58°W., 12.7 ft. scribed "¼ S34 BT". Distance to BT is center measure.</p>
<p>Fd. Brass cap, June 1990 - M 110-39 Fd. OK, Oct. 1992 by Donald Peel - M 115-78 (and M 115-5)</p>
<p>Harvey Christensen, For: Seneca Jones Timber Co. - Dec. 1999 - M 134-4</p> <p>-----</p> <p>Found - 1988 2.5" BC, 7 ft. above ground. PLS 752 17" D.Fir N.60°W., 12.9 ft., healed face. 37" D.Fir South, 72.6 ft., healed face. Set - 15" D.Fir N.28°E., 17.1 ft., blazed & scribed "¼ S34 BT" 17" D.Fir, S.75°E., 34.8 ft., blazed & scribed "¼ S3 BT". Found - 5" pressure treated post 1.5 ft. West.</p>
<p>Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1955, surveyed 2000/2001. (DCSO rec. Vol. 54 page(s) 20829-30)</p>