

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1357)

Set ¼ sec. post, from which
A Fir 18" dia., bears S.57°E., 13 lks. dist.
A Fir 12" dia., bears N.37°W., 41 lks. dist.

Wilford N. Haines - Feb. 1957 - M 4-51

Found NW BT.
Set a 36" T Iron with brass cap inscribed "Survey Point-Wilford N. Haines #239".

Weyerhaeuser survey by McChesney, Jan. 29, 1958 - C.S. File 53/105-37 and Weyerhaeuser cor. report - July 1964 - C.S. File 51/87-8

GL0 survey record, 1855:
Post, gone.
18" Fir S.57°E., 13 lks., not found.
12" Fir N.37°W., 41 lks., bark scribed, also face chopped and scribing visible behind burl.
Haines corner record:
"T" bar with W. Haines cap and 3"x6" Cedar post.
Referenced by G. McChesney (Plates and "W" nails only)
52" Fir N.66°E., 21.2 ft., OK.
16" Fir N.37°W., 27.2 ft., OK.

Fd. OK, July 1988 by D. Peel - M 106-59
Fd. OK, June 1990 - M 110-39

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55 Page(s) 21793-4)

The ¼ sec. cor. of secs. 27 & 34, perpetuated by Haines, in 1957, and by McChesney, in 1958, monumented with an iron T-post, 1" sq., firmly set, buried 3" below ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree
A fir snag, size indeterminate, bears N.37°W., 27.1 ft., with scribe marks ¼ S visible.
and the remains of a bearing tree mkd. by McChesney
A sawed fir stump, 56" dia., bears N.67½°E., 22.3 ft., with axe marks visible.

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

and bearing tree mkd. by person(s) unknown
A fir, 19" dia., bears S.29½°W., 4.3 ft., with a healed double blaze.
At the cor. point
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the T-post, with brass cap mkd.
T22S R4W
¼ $\frac{S27}{S34}$
2007
from which new bearing tree
A fir, 12" dia., bears N.35¾°E., 29.3 ft., mkd. ¼ S27 BT.