

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Wm. Thiel under Contract #321 dated April 11, 1879 - (DCSO records Vol. 4 Page(s) 1359)

Set ¼ sec. post, from which
A Fir 14" dia., bears S.11¼°E., 31 lks. dist.
A Fir 12" dia., bears N.62 ¾°W., 44 lks. dist.

Wilford N. Haines - Feb. 1957 - M 4-51

Point for corner located by proportional measurement.
Set a 36" T Iron with brass cap inscribed "Survey Point - Wilford N. Haines #239, from which
30" Incense Cedar S.45°E., 82.3 ft.
14" D.Fir N.44°E., 34.0 ft.

Douglas Co. Surveyors Office - Gregory Quibell Deputy - Karen Reed; Terrie Franssen; Ed Sehlin - Oct. 4, 1982 - C.S. 62/1-21

Found - 36" "T" Iron with brass cap. Monument was protruding 6" out of ground.
30" I.Cedar now 32" stump, bears S.45°E., 82.3 ft. Shows good scar.
14" Fir now 21", alive, bears N.46°E., 34.3 ft. (Rec. N.44°E., 34.0 ft.) Shows good scar.
I referenced location of found monument then replace it with: 1" x 30" Iron pipe with brass cap attached mkd. "Douglas Co Surveyor T22S 1/4 S22 S27 R4W 1981". I place found "T" Iron along northerly side and slightly lower than new brass cap. Monument is located 0.8 ft. North of corner post of a new wire fence running South and N.66°E.
New BTs -6" Fir scribed "¼ S27 CS BT" in double blaze, bears S.31°W., 41.6 ft.
7" Fir scribed "¼ S27 CS BT" in double blaze, bears S.82°W., 21.8 ft.
14" Fir scribed "¼ S22 CS BT" in double blaze, bears N.46°W., 20.4 ft.

Fd. Ok - Bruce Shaner - 07/23/97 - M 127-26 & C.S. 65/15-8B

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO recs Vol. 55 Pgs 21798-9)

The ¼ sec. cor. of secs. 22 & 27, reestablished by proportionate measurement by Haines, in 1957, perpetuated by Quibell, in 1982; there is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron post, 1¼" dia., cont.

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

firmly set, projecting 7" above ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Haines

A sawed fir stump, 29" dia., bears N.46½°E., 34.7 ft., with a healed blaze.

A sawed cedar stump, 19" dia., bears S.46½°E., 81.7 ft., no marks visible.

and remains of bearing trees mkd. by Quibell

A fir, 13" dia., bears S.31¾°W., 40.9 ft., with a healed blaze.

A fir, 12" dia., bears S.83½°W., 22.1 ft., with a healed double blaze.

A fir snag, 24" dia., bears N.45¾°W., 20.4 ft., with a healed double blaze.

and a new bearing tree

A fir, 14" dia., bears N.56½°W., 99.0 ft., mkd. ¼ S22 BT.