

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1356)

-----  
Set ¼ sec. post, from which  
A Fir 4" dia., bears S.10°E., 20 lks. dist.  
A Fir 8" dia., bears N.14°E., 23 lks. dist.

-----  
Wilford Haines - For E.G. Whipple property - (Date ?)  
(Received for Haines Estate and filed Sept. 1990) - H. En 6

-----  
1" Iron pipe.  
Fir 4", S.10°E., 20 lks.  
Fir 8" N.14°E., 23 lks.  
Had to set this corner.

-----  
BLM resurvey by Wayne L. Rogers, Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1415, Surveyed Jan. 7/March 29, 1988 - (DCSO records Vol. 48 Page(s) 18622-23)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 22 S R 4 W  
¼      S 15  
         S 22  
         1988

from which  
A Fir 32" dia., bears N.1½°E., 91 lks. dist. mkd. ¼ S15 BT  
A Fir 10" dia., bears S.17°E., 90 lks. dist. mkd. ¼ S22 BT  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point unofficially established as the ¼ sec. cor. of secs. 15 and 22 by a Bureau of Land Management administrative survey, date unknown, and is not accepted, bears S.20°30'E., 0.220 chs. dist., monumented with an iron pipe 1/2" dia., firmly set, projecting 8" above ground.