

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1360)

Set post, 4" dia., 4 ft. long, with marked stone 12" in ground for qr. sec. cor., marked ¼ S on N. face, from which
A Maple 12" dia., bears S.2°E., 61 lks. dist. mkd. ¼ S BT
A Fir 40" dia., bears N.39°W., 35 lks. dist. mkd. ¼ S BT.

William L. Wilt - For: Weyerhaeuser Co. - Jan. 18, 1963 - C.S. File 53/105-7

GLO survey record, 1884:
12" Maple S.2°E., 61 lks.; 24" Maple, face opened, scribed "¼S" visible.
40" Fir N.39°W., 35 lks.; 48" Fir, recent windfall; apparently bark scribing burned off. Only tree in proper position.
1955 Survey record:
Squared stake set by Clyde Randall for W.A. Woodard Co. and marked ¼ S; stake remains, is above ground about 1 ft. and contains hub tack.
Accessories added this date: ("W" nails and plates)
20 Cedar N.29°E., 56.2 ft.
24" Maple S.8°E., 40.2 ft. (Orig. BT) measured to center of tree)

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Jan. 1965 - C.S. File 53/101-73

Found - Orig. 12" now 24" snag, Maple, S.2°E., 40.3 ft., shows scribing "BT".
Orig. 40" Fir, now uprooted stump, N.39°W., 35 lks.
Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 4 W
¼ $\frac{S}{S}$ $\frac{10}{15}$
1965
New BTs -42" Fir N.53°W., 89.0 ft. mkd. ¼ S10 BT.
30" Cedar N.23°E., 55.2 ft. mkd. ¼ S10 BT.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor,
and Robert H. Browning, Surveying Tech. Group No. 2170
surveyed Aug. 2007/Feb. 2008 - (DCSO recs Vol. 55 Pg 21803)

The ¼ sec. cor. of secs. 10 and 15, perpetuated by Randall,
in 1955, subsequently perpetuated by Wilt, in 1963, further
perpetuated by Rogers, in 1965, monumented with an iron post,
1¼" dia., firmly set, projecting 8" above ground, with brass
cap (properly) mkd.

from which the remains of the original bearing trees

A decayed maple root crown, size indeterminate, bears
S.2°E., 40.3 ft., no marks visible.

A root hole bears N.39°W., 23.1 ft., with an uprooted,
sawed, decayed fir stump, 43" dia., lying alongside, no
marks visible.

and the remains of bearing trees mkd. by Bruce Rogers

A sawed, decayed cedar stump, 26" dia., bears N.24¼°E.,
55.5 ft., no marks visible.

A sawed, decayed fir stump, 41" dia., bears N.51°W., 88.7
ft., no marks visible.

and new bearing trees

A fir, 12" dia., bears N.75¾°E., 13.9 ft., mkd. ¼ S10 BT.

A fir, 9" dia., bears S.10¼°W., 19.6 ft., mkd. ¼ S15 BT.