

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 3

Alias	Description

BLM Resurvey, by Dale B. Bedell, Surveyed under Group No. 1703. Surveyed Aug. 1993 thru May 1994. (D.C.S.O. records Vol. 52 Page(s)19650)

-----  
Point for the center ¼ sec. cor. of sec. 3, at intersection with the E. and W. centerline.  
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T22S R4W  
C 1/4 S 3  
1994

from which  
A hemlock, 16 ins. diam., bears S.36°W., 12½ lks. dist., mkd. C 1/4 S3 BT.  
A yew, 6 ins. diam., bears N.18°W., 3½ lks. dist., mkd. C 1/4 S3 BT.

Corner report by Daniel Baker - For: Weyerhaeuser Co. - Jan. 1995 - M 119-54

-----  
Found - US BLM brass cap dated 1994.  
5" yew, N.8°W., 2.6 ft. to spike, scribe visible. (Rec. BLM tag reads S.18°E.)  
15" Hemlock S.39°W., 8.1 ft. to spike, scribe visible. (Rec. BLM tag reads N.36°E.)  
Set 6 ft. fence post 1 ft. East.  
Spikes were set this survey at side center.