

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; and 2 & 3, T23-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - James E. Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 6 Page(s) 2266 and page 2269)

Set post cor. to secs. 2, 3, 34 and 35, from which
A W.Oak 30" dia., bears N.78°W., 235 lks. dist.
A Laurel 10" dia., bears N.41°E., 136 lks. dist.
A Maple 8" dia., bears S.30°E., 180 lks. dist.
A W.Oak 11" dia., bears S.29°W., 85 lks. dist.

Survey by Wilford N. Haines - For: Whipple Mill - June 1961
-M 22-6 and M 39-53

Found - 12" Fir S.40°E., 70.0 ft.
14" Fir S.66°E., 69.2 ft., not scribed and no record
of renewal.
Set 1" x 1" x 36" T-Iron and scribed
5" W.Oak S.73°W., 33.3 ft.

Douglas County Surveyors Office - Gregory Quibell, Deputy -
Terrie Plouff, wit. - Dec. 21, 1981 - C.S. File 61/30-2

Found - 1" x 1" x 36" T Iron with Haines brass button,
firmly set, flush with the ground.
5" now 11" W.Oak bears S.73°W., 33.7 ft. (Rec. 33.3
ft.) with good scar visible.
12" now 20" Fir with scribed "T" visible in
previously opened blaze, bears S.40°E., 70.0 ft.
14" now 23" Fir with large partially healed blaze
with rotted face, bears S.66°E., 69.2 ft.

In my research for this cor., I could not find any
information as to the origin of the two Fir BTs. The only
filed survey prior to M 22-6 and M 39-53, is M 2-60 which
does not mention either tree.

I reference the location of the found T Iron and SET a 1" x
30" I.P. with brass cap attached in its place. Brass cap is
stamped: "Douglas Co Surveyor 1981 T22S R4W T23S S34 S35 S3
S2". I place found T Iron along East edge of brass cap.

New - Power pole #4-191 bears N.34°W., 154.0 ft. with DCSO
BT tag attached.
4" Pole fence corner bears S.70°E., 6.3 ft. with
DCSO BT tag attached.

(See sketch in C.S. File)

Fd. OK, Oct. 1992 by Donald Peel - M 115-78
Ken Hoffine - For: Lone Rock Timber Co. - 10/2000 - M 135-69

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; and 2 & 3, T23-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1955, surveyed 2000/2001. (DCSO rec. Vol. 54 page(s) 20830-1)

The cor. of secs. 2, 3, 34, & 35, restored by person(s) unknown, perpetuated by Haines, in 1961, further perpetuated by Quibell, in 1981. There is no remaining evidence of the original corner, therefore this point is accepted as the corner, monumented with an iron pipe, 1" dia., firmly set, projecting 12" above ground, alongside a 1 x 1" "T" shaped iron rod, firmly set, projecting 6" above ground, from which bearing trees mkd. by person(s) unknown and reported by Haines

A fir, 28" dia., bears S.62 $\frac{3}{4}$ °E., 69.4 ft., with healed double blaze.

A fir, 26" dia., bears S.39 $\frac{3}{4}$ °E., 71.0 ft., with healed double blaze.

and a bearing tree mkd. by Haines

An oak, 15" dia., bears S.74 $\frac{1}{4}$ °W., 33.5 ft., with a healed blaze

and an accessory by Quibell

A power pole, No. 4-191, bears N.33°W., 155.9 ft.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " diam., 27" in the ground, with brass cap mkd.

T22S R4W
S 34 | S 35
S 3 | S 2
T 23 S
2001

Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron pipe and the "T" shaped iron rod on north side of the stainless steel post.