

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec Cor for 26, 27, 34 and 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1356)

Set post cor. of secs. 26, 27, 34 and 35, from which
A Fir 12" dia., bears N.14°E., 15 lks. dist.
A Fir 10" dia., bears N.20°W., 27 lks. dist.
A Fir 12" dia., bears S.82°W., 165 lks. dist.
A Laurel 6" dia., bears S.20°E., 39 lks. dist.

Fd. and used in GLO survey by Wm. P. Wright, under Contract #514, dated Aug. 27, 1884 (DCSO records, Vol. 4 Page 1369)

GLO survey by Oscar F. Thiel, Deputy Surveyor, under special instructions dated August 15, 1901 (DCSO records Vol. 4 Page(s) 1374-75)

The Sec. Cor., having disappeared, I re-establish it by setting a Cedar Post, 3 ft. long, 4" sq., 24" in the ground, marked T22S S26 on NE.; R4W S35 on SE.; S34 on SW. and S27 on NW. faces, with 1 notch on S. and 2 notches on E. faces, from which

A Fir 10" dia., bears S.80°E., 32 lks. dist. mkd. T22S R4W S35 BT.

The original bearing tree having fallen; all the others as described by the surveyor general.

O.F. Thiel - Feb. 5, 1947 - Thiel Field Book 3 Page 12

Two witness trees standing. NE. and NW trees.

Wilford N. Haines - Feb. 1957 - M 4-51

Found old BTs.

Set a 36" T Iron with brass cap inscribed "Survey Point - Wilford N. Haines #239".

Glen McChesney - For: Weyerhaeuser Co. - Jan. 29, 1958 - C.S. File 53/105-38

GLO Survey record, 1855:

Post, no trace.

12" Fir N.14°E., 15 lks.; Bark scribed.

12" Fir S.82°W., 165 lks.; double stump, burned.

10" Fir N.20°W., 27 lks.; face chopped, burlled over.

6" Laurel S.20°E., no trace.

(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec Cor for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found:

3/4" Galv. pipe and T Iron with Haines cap.
Accessories added this date: ("W" nails and plates)
38" Fir N.14°E., 8.2 ft. (Orig. BT)
24" Fir S.76°E., 27.3 ft.
20" Fir N.18°W., 17.3 ft. (Orig. BT)
14" Fir S.40°W., 37.2 ft.

Cor. Fd. OK, B.Rogers, DCSO - Feb. 1965 C.S. File 53/101-77
FD. OK, by David Wellman, May 23, 1997 - M 127-14

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55 Page(s) 21783)

The cor. of secs. 26, 27, 34, & 35, perpetuated by Haines, in 1957, monumented with an iron T-post, 1" sq., firmly set, projecting 11" above ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remaining orig. BTs

A fir, 50" dia. bears N.14°E., 9.9 ft. with a healed blaze
A fir, 35" dia. bears N.20°W., 17.8 ft with a healed blaze
and BTs mkd. by McChesney, in 1958

A fir, 39" dia. bears S.75¼°E. 27.3 ft with a healed blaze
A fir, 38" dia. bears S.39¾°W. 37.3 ft with a healed blaze

At the cor. point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the T-post, with brass cap mkd.

T22S R4W
S27|S26
S34|S35
2007