

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, Deputy Surveyor, under special instructions dated August 15, 1901 (DCSO records Vol. 4 Page(s) 1375-76)

-----  
Set a Cedar post 3 ft. long, 3" sq., with marked stone 24" in the ground for ¼ sec. cor. mkd. ¼ S27 on W. face and 26 on E. face, from which  
    A Fir 16" dia., bears N.21°E., 37 lks. dist. mkd. ¼ S26 BT  
    A Fir 40" dia., bears N.9°W., 56 lks. dist. mkd. ¼ S27 BT.  
This corner stands in ravine, bearing E. and W. and is 175 ft. below top of ridge.

Wilford N. Haines - Feb. 1957 - M 4-51

-----  
Found old BTs.  
Set a 36" T Iron with brass cap inscribed "Survey point - Wilford N. Haines #239."

Douglas Co. Surveyors Office - Larry E Monrean, Deputy - Randall Smith; Stephen Flause - April 27, 1987 - C.S. 62/40-19

-----  
Found - A Haines T Iron with metal washer protruding 1 ft. above ground, bent slightly West.  
Original stone not found.  
16" now 34" dia. 5 ft. high D.Fir stump. We open and find scribing "BT" upper face shows good axe marks. Scribing possibly chopped out, bears N.21°E., 25.6 ft. (Rec. N.21°E., 24.4 ft. possible face measurement.) Orig. BT.  
40" now 38" dia. 4 ft. high D.Fir stump, axe marks and flat spots found on bark. We open and found no burl, blazes, axe marks or scribing. Bears N.9°W., 38.8 ft. (Rec. N.9°W., 37.0 ft., possible face measurement) Possible original BT.  
Set a DCSO 2 3/8" brass cap on a 1" I.D. x 32" long iron pipe, protrudes 6" above ground, marked "Douglas County Surveyors Office T22S ¼ S27 S26 R4W 1987". Haines 36" long T Iron protrudes 4" above ground, reset along North edge of BC/IP. DCSO BC/IP set at found plumb position of T-Iron.  
New BTs -37" dia. 4 ft. high D.Fir stump, set a boat spike through BT tag, bears S.36°W., 61.2 ft.  
    34" dia. 1½ ft. high Cedar stump, set a boat spike through at tag, stamped "BO 1" bears N.46°E., 47.9 ft.  
Corner lies in a clear cut at bottom of an easterly-westerly ravine.

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55 Page(s) 21784)

-----

The ¼ sec. cor. of secs. 26 & 27, perpetuated by Haines, in 1957; subsequently perpetuated by Monrean in 1987, monumented with an iron post, 1¼" dia., firmly set, projecting 5" above ground (alongside of which is an iron T-post, 1" sq., with brass washer on top), with brass cap (properly) mkd.

from which the remains of the original bearing trees

A sawed decayed fir stump, 35" dia., bears N.21°E., 24.4 ft., no scribe marks visible on opened decayed blaze.

A sawed decayed fir stump, 33" dia., bears N.9°W., 37.0 ft., no scribe marks visible on opened decayed blaze.

and references by Monrean

A cedar stump, 30" dia., bears N.45¾°E., 47.8 ft. to a boat spike in top center, no marks visible.

A fir stump, 43" dia., bears S.37°W., 61.4 ft. to a boat spike in top center, no marks visible.

and new bearing trees

A fir, 9" dia., bears S.64¾°E., 9.4 ft., mkd. ¼ S26 BT.

A fir, 8" dia., bears S.31¼°W., 22.2 ft., mkd. ¼ S27 BT.