

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Wm. Thiel under Contract #321 dated April 11, 1879 - (DCSO records Vol. 4 Page(s) 1358-59)

Set post for cor. of secs. 22, 23, 26 and 27, from which
A Fir 60" dia., bears S.70½°E., 21 lks. dist.
A Hemlock 24" dia., bears S.61°W., 23 lks. dist.
A Fir 52" dia., bears N.19½°W., 41 lks. dist.
A Fir 8" dia., bears N.26°E., 11 lks. dist.

Fd. and used in GLO survey by Wm. P. Wright, under Contract #514, dated Aug. 27, 1884 (DCSO records, Vol. 4 Page 1371)

GLO survey by Oscar F. Thiel, Deputy Surveyor, under special instructions dated August 15, 1901 (DCSO records Vol. 4 Page(s) 1375)

The Sec. Cor. which having disappeared, I re-establish by setting a Fir post, 3 ft. long, 4" sq., 24" in the ground for cor. mkd. T22S S23 on NE.; R4W S26 on SE.; S27 on SW. and S22 on NW. faces, with 2 notches on S. and E. faces, all witnessed as described by the surveyor general.

Wilford N. Haines - For: Whipple property - Feb. 1957 - M 4-51 and H. En. 6 (and H-112)

M 4-51; H. En. 6
Found old BTs.
Set a 36" T Iron with brass cap inscribed "Survey Point-Wilford N. Haines #239".
H-112
New BTs -26" Fir, South, 15.6 ft.
48" Cedar N.64°W., 44.0 ft.

Douglas County Surveyors Office - Gregory Quibell, Deputy - Karen Reed; Terrie Franssen; Ed Sehlin - Oct. 4, 1982 - C.S. File 62/1-22

Found - 3/4" Iron pipe, unknown origin, alongside 36" T Iron (Haines)
Possible orig. 60" Fir, now 60", alive, with bark scribing "T22S R4 S26 BT". This does not appear to be original scribing. Tree bears S.56°E., 16.0 ft. (Rec. S.70½°E., 13.9 ft.)
Possible original 52" Fir, now 48" stump. No definite scar showing but I open with saw anyway. No face visible. If tree had been bark scribed, logging would have destroyed it. Tree bears N.26°W., 26.9 ft. (Rec. N.19½°W., 27.1 ft.)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

24" Fir, unknown origin, scribed "T22S R4W S27 363" in bark. Tree bears S.4°E., 15.8 ft. (Note: based on my bearing, tree should have been scribed S26, not S27)
48" Cedar, unknown origin, bark scribed "T22S R4W S22 BT". Tree bears N.65°W., 43.7 ft.
(BTs of "unknown origin" were recorded from Haines Estate after this renewal visit)
Since I found no evidence to prove that the two big Firs were originals, I did not change the location of the corner but instead referenced the point set by Haines.
SET a 1"x30" Iron pipe with brass cap attached mkd: "Douglas Co Surveyor T22S S22 S23 S27 S26 R4W 1982" at that location. I reset found 3/4" I.P. and "T" iron alongside new brass cap.
New BT - 7" Fir scribed "T22S R4W S23 CS BT" in double blaze, bears N.67°E., 28.4 ft.

Fd. Ok - Bruce Shaner - 07/23/97 - M 127-26 & C.S. 65/15-8A
Except for the 60" Fir BT & the 48" Cedar BT have miraculously become stumps
Fd OK by B. Shaner, Sept. 2001 - M137-19 & CS65/37-21D

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO recs Vol. 55 Pgs 21786-7)

The cor. of secs. 22, 23, 26 & 27, perpetuated by Haines, in 1957, subsequently perpetuated by Quibell in 1982, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A sawed fir stump, 59" dia., bears S.55¼°E., 16.2 ft., with axe marks visible. (Record, S.70½°E., 13.9 ft.)
A sawed fir stump, 42" dia., bears N.22¾°W., 27.1 ft., with no marks visible on opened blaze. (Rec. N.19½°W.)
and the remains of bearing trees mkd. by Haines
A fir, 34" dia., bears S.4°E., 15.2 ft., with fragmentary scribe marks visible on the bark.
A sawed cedar stump, 50" dia., bears N.63½°W., 44.2 ft., no marks visible.
and a bearing tree mkd. by Quibell
A fir, 8" dia. bears N.68¾°E., 27.9 ft with a healed blaze
and new bearing trees
A fir, 9" dia. bears S.51¼°W., 4.3 ft mkd. T22S R4W S27 BT
A fir, 13" dia. bears N.13¾°W. 20.2 ft mkd T22S R4W S22 BT