

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1354)

-----  
Set post cor. of secs. 22, 23, 14 and 15, from which  
A Fir 36" dia., bears S.77°W., 22 lks. dist.  
A Fir 24" dia., bears N.47°W., 18 lks. dist.  
A Fir 10" dia., bears N.54°E., 20 lks. dist.  
A Fir 12" dia., bears S.52°E., 50 lks. dist.

Fd. and used in GL0 survey by Wm. Thiel under Contract #321 dated April 11, 1879 (DCSO records, Vol. 4 Page 1357)

Wilford N. Haines - For: Whipple property - (Date?) Filed Sept. 1990, received from Haines estate) - H. En. 6

-----  
1" Iron pipe, from which  
Fir 36" S.77°W., 22 lks., found.  
Fir 24" N.47°W., 18 lks., found.  
Fir 10" N.54°E., 20 lks., found.  
Fir 12' S.52°E., 50 lks., found.

Nick Juliano - For: Weyerhaeuser Co. - Nov. 1958 - C.S. File 53/105-12

-----  
GL0 survey record, 1879:  
Post, 2"x2"x2 ft. Yew post, found.  
10" Fir N.54°E., 20 lks.; gone.  
12" Fir S.52°E., 50 lks.; Fd. 28" Fir.  
36" Fir S.77°W., 22 lks.; Fd. 48" Fir.  
24" Fir N.47°W., 18 lks.; Fd. 32" Fir.  
Found 3/4" I. Pipe.  
Accessories added this date: (with "W" nails and plates)  
20" Fir N.76°E., 20.4 ft.  
28" Fir S.52°E., 38.0 ft. (Orig. BT)  
48" Fir S.70°W., 13.0 ft. (Orig. BT)  
32" Fir N.51°W., 9.9 ft. (Orig. BT)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - Sept. 1962 - C.S. File 49/42-60

-----  
Found - Haines T Iron and cap at corner.  
Dead Fir snag, now 36" N.47°W., 11.9 ft. Cut open and found good scribing "T" on small portion of old face.  
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

36" Fir S.77°W., 14.5 ft., uprooted and down.  
Fir, now approx. 30" S.52°E., 33.0 ft., uprooted and down.  
No trace of orig. NE. BT, recently scribed 22" D.Fir N.75°E., approx. 25 ft., not chained, scribed T22S R4W S14 BT in wood and "363".  
Did Not Set Brass Cap.  
New BTs -12" D.Fir S.68°W., 50.3 ft. mkd. T22S R4W S33 CS BT  
19" D.Fir N.42°W., 87.6 ft. mkd. T22S R4W S15 CS BT  
No trees available in SE. quadrant.

Cor. OK, BBR of DCSO, Jan. 1965 C.S. File 53/101-81

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1415, Surveyed Jan. 7/March 29, 1988 - (DCSO records Vol. 48 Page(s) 18621-22)

-----

At Sec. cor., perpetuated by Haines, date unknown, and further perpetuated by Leo J. Martin, date unknown, subsequently perpetuated and recorded by Godfrey in 1962, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 10" above ground, with washer mkd. WILFORD N HAINES DRAIN OR 239, alongside of which is an iron pipe, ½" dia, firmly set, projecting 4" above ground, from which the remains of the original bearing trees:

- A root hole bears S.52°E., 50 lks. dist., with a down Fir alongside, size indeterminate, no marks visible.
- A root hole bears S.77°W., 22 lks. dist. with a down Fir alongside, size indeterminate, no marks visible.
- A Fir snag 36" dia., bears N.47°W., 18 lks. dist. with fragmentary scribe marks visible on opened blaze.

and the remains of a bearing tree mkd. by Martin:

- A sawed Fir stump 21" dia., bears N.75°E., 32 lks. dist. with scribe marks 22S R4W S14 visible on partially healed blaze.

and the bearing trees mkd. by Godfrey:

- A Fir 31" dia., bears N.42°W., 133 lks. dist. with healed double blaze.
- A Fir 18" dia., bears S.68°W., 76 lks. dist. with healed double blaze.

At the corner point  
Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron pipe and T iron, with brass cap mkd:  
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

T 22 S R 4 W  
S 15 | S 14  
S 22 | S 23  
1988

from which new bearing trees:

A Fir 10" dia., bears N.54½°E., 8 lks. dist. mkd. T22S R4W S14 BT.

A Fir 11" dia., bears S.23°E., 21 lks. dist. mkd. T22S R4W S23 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. Brass cap & 5 BTs by Dan Baker, 9/2008 - M156-79

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55 Page(s) 21789-90)

-----  
The cor. of secs. 14, 15, 22, & 23, monumented with a stainless steel post, 2½" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A root hole bears S.52°E., 33.0 ft., with pushed over fir stump, 30" dia., lying alongside, no marks visible.

A root hole bears S.77°W., 14.5 ft., with pushed over fir stump, size indeterminate, lying alongside, no marks visible.

A fir snag, 35" dia., bears N.47°W., 11.9 ft., with axe marks visible.

and the remains of a BT mkd. by Juliano, in 1958, (Record, incorrectly attributed to Leo J. Martin by Rogers and Moore.)

A decayed fir snag, size indeterminate, bears N.75°E., 21.1 ft., no marks visible.

and BTs mkd. by Godfrey, in 1962, reported by Rogers & Moore

A fir, 24" dia., bears S.68°W., 50.2 ft., no marks visible.

A fir, 43" dia., bears N.42°W., 87.8 ft., with a healed blaze.

and bearing trees mkd. by Rogers and Moore

A fir, 16" dia., bears N.54½°E., 5.3 ft., with a healed blaze.

A fir, 18" dia. bears S.23°E., 13.9 ft with a healed blaze