

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1354)

Set ¼ sec. post, from which
A Fir 8" dia., bears N.35°W., 4 lks. dist.
An Alder 12" dia., bears S.30°E., 18 lks. dist.

Corner report from Weyerhaeuser Company - Feb. 22, 1963 - C.S. File 53/105-35

GLO survey record, 1855
12" Alder S.30°E., 18 lks., Gone.
8" Fir N.35°W., 4 lks., Gone.
Set ¾" Iron pipe and Woodard Cedar post and 1" alum. pipe.
Accessories added this date: (Plate and "W" nails)
42" Fir stump N.32°E., 47.5 ft.
40" Red Cedar snag, N.27°W., 3.9 ft.
(Corner history and affidavit):
In 1940 John Woodward and Chester Gilham were at this corner. They set a red cedar post from the Fir BT which was a snag and in poor condition. They remembered the tree was small and suppressed in growth by a 36" red cedar tree which was growing next to and around the base of the fir BT showing old scribe marks. They put their cruiser marks on the East side of this cedar tree. The alder BT was gone. Feb. 22, 1963, I took John Woodard and Chester Gilham to this corner and they pointed out the hole at the base of a 42" red cedar snag with their cruiser marks on it. The cedar post was recovered from beneath the debris. (Affidavit from Mr. Woodward is in C.S. File)

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Jan. 1965 - C.S. File 53/101-68

Found - ¾" I.Pipe set by Weyerhaeuser.
60" Fir stump N.32°E., 47.5 ft. "W" brass plate mkd. Eng. #2149.
40" Cedar snag N.27°W., 3.9 ft. "W" brass plate mkd. Eng. #2149.
No trace of original BTs.
New BT - 15" Cedar S.88°W., 10.5 ft. mkd. ¼ S15 CS BT.

Dan Baker - For: Weyerhaeuser Co. - 9/2008 - M156-79

Found - ¾" IP per C.S. 53/105
48" Fir stump, N.32°E., 47.5', 1963 Weyco BT.
continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - 26" Cedar, S.88°W., 10.6 ft., closed face 1965 DC BT
14" Fir, N.79°E., 16.5 ft., scribed "¼ S14 BT"
10" Alder, S.9°E., 10.7 ft., bark scribed "¼ S14 BT"
7" Fir, N.23°W., 28.4 ft., scribed "¼ S15 BT"

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55 Page(s) 21791-2)

The ¼ sec. cor. of secs. 14 & 15, perpetuated by Woodward and Gilham, in 1940, from original evidence no longer in existence, Woodward affidavit filed in the Douglas County Surveyor's Office, C.S. File No. 53/105, subsequently perpetuated by Wilt, in 1963, monumented with an iron pipe, 1" dia., firmly set, projecting 9" above ground, from which the remains of the references by Wilt

A sawed, decayed fir stump, 48" dia., bears N.32½°E., 49.3 ft., no marks visible on an opened blaze.

A sawed, decayed cedar stump, 42" dia., bears N.21½°W., 6.9 ft., no marks visible.

and a bearing tree mkd. by Rogers, in 1965

A cedar, 30" dia., bears West, 10.7 ft., with axe marks visible on open blaze.

and bearing trees mkd. by Baker

A fir, 15" dia. bears N.87°E., 16.6 ft with a healed blaze

An alder, 12" dia., bears S.6½°E., 15.0 ft., with scribe marks W¼ S14 BT visible on bark.

A fir, 7" dia., bears N.23°W., 28.5 ft with a healed blaze

At the cor. point

Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, directly over the iron pipe, with brass cap mkd.

T22S R4W

¼

S15|S14

2007