

PRIMARY CORNER DESCRIPTION Sec Cor for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1354)

-----  
Set post cor. of secs. 10, 11 and 14 and 15, from which  
A Fir 8" dia., bears S.10°E., 37 lks. dist.  
A Laurel 5" dia., bears S.34°W., 20 lks. dist.  
A Fir 8" dia., bears N.15°E., 35 lks. dist.  
A Fir 6" dia., bears N.28°W., 66 lks. dist.

William L. Wilt, Land Agent - For: Weyerhaeuser Co. - Jan. 21, 1963 - C.S. File 53/105-8

-----  
GLO survey record, 1855:  
Post, gone.  
8" Fir S.10°E., 31 lks.; 32" windfall, uprooted face not opened.  
5" Laurel S.34°W., 20 lks.; No trace.  
8" Fir N.15°E., 35 lks., broken off near scribing, scribing visible.  
16" Fir N.28°W., 66 lks., 30" Fir, windfall, 1962 open face and scribing.  
Weyerhaeuser 1957 record:  
26" Fir N.28°W., 43.5 ft., down.  
18" Fir N.41°E., 27.1 ft., down.  
22" Fir S.68°W., 37.0 ft., down.  
40" Fir S.45°E., 44.0 ft. (see new reference)  
Found monel at proper location.  
Accessories added this date: (with plate and "W" nail)  
45" Fir S.48°E., 44.6 ft.  
10" Fir N.23°E., 23.5 ft.  
10" I.Cedar N.71°W., 69.7 ft.  
10" Fir S.39°W., 38.0 ft.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Jan. 1965 - C.S. File 53/101-74

-----  
Found - 3/4" alum. pipe at corner, set by Weyerhaeuser from orig. BTs.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 4 W  
S 10 | S 11  
S 15 | S 14  
1965

New BTs -8" Fir N.58°E., 96.3 ft. mkd. T22S R4W S11 CS BT.  
12" I.Cedar N.71°W., 69.7 ft. mkd. T22S R4W S10 CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

12" Fir S.39°W., 38.0 ft. mkd. T22S R4W S15 CS BT.  
48" Fir S.48°E., 44.6 ft. mkd. T22S R4W S14 CS BT.

Daniel Baker - Sept. 11 1995 - C.S. File 65/1-2  
-----

Found - Douglas Co. Surveyor's Office Brass cap dated 1965,  
with 1957 monel pipe alongside.  
40" Fir stump S.48°E. 44.6 ft to "W" nail - scribing  
visible (rec S.48°E. 44.6 ft - 1963 Weyerhaeuser)  
20" Fir, N.24°E., 24.4 ft. - closed face. (rec.  
N.23°E., 23.5 ft. to "W" nail - 1963 Weyerhaeuser)  
New BTs -13" Fir, S.78°E., 6.2 ft. to "W" nail - scribed  
"T22S R4W S14 BT"  
11" Alder, S.44°W., 8.4 ft. to "W" nail - scribed  
T22S R4W S15 BT"  
9" Fir, N.3°E., 13.1 ft. to "W" nail - scribed T22S  
R4W S11 BT"

BLM Dependent resurvey by A. Bert Skeesick Cadastral  
Surveyor, and Robert H. Browning, Surveying Tech. Group No.  
2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55  
Page(s) 21792-3)  
-----

The cor. of secs. 10, 11, 14, and 15, perpetuated by the  
Weyerhaeuser Company, in 1957, subsequently perpetuated by  
Wilt, in 1963, further perpetuated by Rogers, in 1965,  
monumented with an iron post, 2" dia., firmly set, projecting  
2" above ground, with brass cap (properly) mkd.  
from which the remains of original bearing trees  
A burnt decayed fir stump, size indeterminate, bears  
N.15°E., 23.1 ft., no marks visible.  
A root hole bears S.10°E., 24.4 ft., with a fallen decayed  
fir snag, 30" dia., lying alongside, no marks visible.  
A decayed fir stump, size indeterminate, bears N.28°W.,  
43.6 ft., with fragmentary scribe marks visible on  
remaining center stock.  
and the remains of a bearing tree mkd. by Wilt  
A fir, 25" dia., bears N.24¼°E., 24.3 ft., no marks  
visible on open blaze.  
and the remains of bearing trees mkd. by Bruce Rogers  
A fir, 25" dia., bears N.87°E., 16.6 ft., with a healed  
blaze.  
A sawed decayed fir stump, 47" dia., bears S.47°E., 44.6  
ft., no marks visible.  
A root hole bears S.39¾°W., 38.5 ft., with a fallen  
decayed fir snag, 14" dia., lying alongside, no marks  
visible.

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed cedar snag, size indeterminate, bears N.71°W., 70.0 ft., with marks T22S R4W S10 CS B visible on remaining center stock.  
and BTs mkd. by Baker, in 1995  
A fir, 11" dia., bears N.2¾°E., 13.7 ft., with a healed double blaze.  
A fir, 16" dia., bears S.80°E., 6.7 ft., with a healed blaze.  
An alder, 12" dia., bears S.43¾°W., 9.5 ft., with a healed blaze.  
and a new bearing tree  
A fir, 10" dia., bears N.13¾°W., 17.4 ft., mkd. T22S R4W S10 BT.