

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Closing Cor. for Secs. 2 and 3 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under special instructions dated August 15, 1901 (DCSO records Vol. 4 Page(s) 1376-77)

I set a Cedar post 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 2 and 3, marked CC T22S R4W on S.; S2 on E.; and S3 on W. faces, with 2 grooves on E. and 4 grooves on W. faces, from which
A Hemlock 6" dia., bears S.47°E., 23 lks. dist. mkd. T22S R4W S2 BT.
A Cedar 12" dia., bears S.65°W., 27 lks. dist. mkd. T22S R4W S3 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Clete Putnam & Vernon "Ray" Tracy, crew - March 1962 - C.S. File 49/42-56

Found - Dead Cedar snag, 16", S.65°W., 17.8 ft. scribing visible on old face "CC T22S R". Rest of old face rotted away.

Rotted remains of Hemlock stump S.47°E., 15.2 ft. Too far gone to find scars or scribing.

Set Brass cap at cor. mkd: County Surveyors Office
T22S R4W

CC $\frac{S\ 3\ |S3}{1962}$

New BTs -5" D.Fir S.26°W., 10.2 ft. mkd. S3 CC CS BT.
15" W.Fir S.53°E., 32.1 ft. mkd. T22S R4W CC S2 CSBT

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1026, surveyed July 15, 1980/March 12, 1981 (DCSO records Vol. 44 Page(s) 16969-70)

(39.26 chs.)
True point for the closing cor. of secs. 2 and 3.
Set an Alum. post 28" long 2½" dia., 24" in the ground, with alum. cap mkd: T 21 S R 4 W

$\frac{S\ 35}{S\ 3\ |S\ 2}$
T 22 S | R 4 W
CC
1981

from which
A Fir 10" dia., bears S.65°E., 26 lks. dist. mkd. T22S R4W S2 CC BT.
A Fir 13" dia., bears S.84°W., 55 lks. dist. mkd. T22S R4W S3 CC BT.
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Closing Cor. for Secs. 2 & 3 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

From this point, the original closing cor. of secs. 2 and 3, bears N.1°11'W., 0.078 chs. dist., perpetuated and recorded by Godfrey in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap mkd. as of record

from which the remains of an original bearing tree

A Cedar snag 16" dia., bears S.65°W., 27 lks. dist. with illegible scribe marks visible on partially healed blaze.

and bearing trees mkd. by Godfrey

A Grand Fir 20" dia., bears S.53½°E., 49 lks. dist. with healed double blaze.

A Fir 14" dia., bears S.26°W., 15 lks dist. with healed double blaze.

BLM dependent resurvey by Harvey M. Christensen, LS 2603, under group # 2171, surveyed Nov. 2007/Aug. 2008 - (DCS0 records Vol. 55 Page(s) 21526-7)

The closing cor of secs. 2 & 3, T22S R4W on the S bdy of sec. 35, monumented with an aluminum post, 2½" dia., firmly set, projecting 2" above ground, with aluminum cap mkd

T 21 S R 4 W
S 35
S 3 | S 2
T 22 S | R 4 W
CC
1981

from which the remains of BTs mkd. by Jelley and Rogers

A decayed fir snag, 12" dia., bears S.65°E., 17.2 ft., with illegible scribe marks visible on partially healed blaze.

A fir, 17" dia. bears S.84°W. 36.3 ft. with a healed blaze
No suitable bearing tree available within limits in sec. 2.

From this point, the original closing cor. of secs. 2 & 3, T22S R4W bears N.1°11'00"W., 5.15 ft., reported by Jelly & Rogers, monumented with an iron post, 1¼" dia., firmly set and leaning, projecting 18" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
S 3 | S 2
CC
T 22 S R 4 W
1962

from which the remains of an original bearing tree

A decayed cedar snag, size indeterminate, bears S.65°W., 17.8 ft., no marks visible. continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Closing Cor. for Secs. 2 and 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of BTs mkd. by Godfrey, in 1962, reported by Jelly and Rogers

A G.Fir snag, 20" dia., bears S.53½°E., 32.3 ft., no marks visible.

A Fir, 13" dia., bears S.26°W., 9.9 ft., with a healed blaze. (Record, 14" dia.)

Set 5 ft. steel fence post alongside cor.