

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1369)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for qr. sec. cor., marked ¼ S on N. face, from which
A Fir 8" dia., bear N.82°W., 19 lks. dist. mkd. ¼ S BT.
A Laurel 5" dia., bears S.30°E., 10 lks. dist. mkd. ¼ S BT.

O.F. Thiel - For: H.W. Kissling - April 16, 1947 - Thiel's Field Book 3 Page 34

NW BT standing, newly cut in marks plain. Laurel tree dead. Set a Fir stake.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Jan. 27, 1965 - C.S. File 53/101-76

Found - 3/4" galv. I.Pipe at corner.
Orig. BT, 8" Fir, now 18" snag, N.82°W., 12.5 ft. Scar shows good scribing "¼".
No trace of SE. BT.
New BTs -13" Cedar S.12°W., 88.0 ft. mkd. ¼ S35 CS BT.
9" Cedar N.59°E., 27.3 ft. mkd. ¼ S26 CS BT.

Survey by Donald Peel, LS #752 - For: Weyerhaeuser Co. - July 1988 - M 106-59

Corner Report Only
Found - 3/4" iron pipe in mound of stone.
17" I.Cedar, N.61°E., 24.8 ft., opened to visible scribing. (Not of our record)
9" Fir S.15½°E., 8.5 ft. Weyerhaeuser tag. (Not of our record)

Fd. OK by David Wellman - 5/23/97 - M 127-14