

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 2; and 35 of T21-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 751)

Set ¼ sec. post, from which
A Fir 36" dia., bears N.30°E., 4 lks. dist.
A Fir 30" dia., bears S.4°W., 24 lks. dist.

Survey by Glen McChesney - For: Weyerhaeuser Co. - 1958-59 - C.S. File 53/1-40

(It appears from the study of the GLO plats that this is a common corner.)
Post not found.
Found - 36" Fir N.30°E., 4 lks., now 58" Fir, bark scribing visible.
30" Fir S.4°W., 24 lks., now 48" Fir, bark scribing visible.
Set Monel Pipe for corner.
Referenced by Weyerhaeuser method:
47" Fir S.4°W., 15.1 ft. Orig. BT.
58" Fir N.29°E., 1.7 ft. Orig. BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy and crew - Nov. 16, 1964 - C.S. File 49/68-41

(On N. line T22S R4W and on Lane-Douglas County Line)
Found - 1/2" galv. iron pipe extending 12" above ground.
42" Fir stump S.4°W., 15.8 ft., old bark scribing visible "¼ S".
Fir stump, uprooted, N.30°E., 2.6 ft., no scribing found.
Did Not Set Brass Cap
New BTs -17" W. Fir N.76°W., 27.7 ft. mkd. ¼ S35 CS BT.
10" D. Fir N.49°E., 49.7 ft. mkd. ¼ S35 CS BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1026, surveyed July 15, 1980/March 12, 1981 (DCSO records Vol. 44 Page(s) 16951-52)

At 1/4 cor., perpetuated and recorded by Godfrey, 1964, monumented with an iron poist, 2½" dia., firmly set, projecting 6" above ground, with brass cap mkd.

T 21 S R 4 W
1/4 $\frac{S \ 35}{S \ 2}$
T 22 S R 4 W
1965

(Cont. Next Page)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

from which the remains of the original bearing trees
A root hole, bears N.30°E., 4 lks. dist. with a downed
sawed Fir stump alongside 38" dia., with fragmentary
scribe marks visible on opened blaze.
A sawed Fir stump 35" dia., bears S.4°W., 24 lks. dist.
with fragmentary scribe marks visible on bark.
bearing trees mkd. by Godfrey:
A Fir 22" dia. bears N.49°E. 79½ lks w/healed double blaze
A Fir 25" dia. bears N.73°W. 40 lks. w/healed double blaze
and a bearing tree mkd. by Jelley:
A grand Fir 7" dia., bears S.3°E., 147 lks. dist. with
healed blaze.
and a new bearing tree:
A Fir 7" dia., bears S.16½°W., 22 lks. dist. mkd. ¼ S2 BT.

BLM dependent resurvey by Harvey M. Christensen, LS 2603,
under group # 2171, surveyed Nov. 2007/Aug. 2008 - (DCS0
records Vol. 55 Page(s) 21525-6)

The ¼ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.,
monumented with an iron post, 2½" dia., firmly set,
projecting 6" above ground (alongside of which is an aluminum
pipe, ½" dia., firmly set, projecting 6" above ground), with
brass cap (properly) mkd.
from which the remains of an original bearing tree
A sawed fir stump, 35" dia., bears S.4°W., 15.8 ft., with
illegible scribe marks visible on bark.
and BTs mkd. by Godfrey, in 1964, reported by Jelly in 1965
A D.Fir, 32" dia., bears N.49°E., 50.8 ft., with a healed
double blaze. (Record, 52.5 ft.)
A D.Fir, 32" dia., bears N.73°W., 24.2 ft., with a healed
double blaze. (Record, 26.4 ft.)
and the remains of a bearing tree mkd. by Jelley
A sawed grand fir stump, 24" dia., bears S.3°E., 97.0 ft.,
with healed blaze.
and the remains of a bearing tree mkd. by Jelley and Rogers
A sawed fir stump, 11" dia., bears S.19°W., 14.5 ft., with
healed blaze. (Record, S.16½°W.)
and a reference monument, by William D. Robinson, Registered
Land Surveyor, No. 1554, in 2003, filed in Survey Corner
Reestablishment No. 14340, Records of Lane County
An iron rod, 5/8" dia., firmly set, projecting 2" above
ground, bears S.18°16'W., 28.5 ft., with an aluminum
cap mkd. LCS RP 1.
Set 5 ft. aluminum fence post alongside cor.