

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 2; 35 & 36, T21-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

NOT IN DOUGLAS COUNTY

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 751)

Set post cor. of secs. 1, 2, 35 and 36, from which
A Fir 7" dia., bears S.60°W., 16 lks. dist.
A Fir 8" dia., bears N.11°E., 71 lks. dist.
A Fir 20" dia., bears S.62°E., 120 lks. dist.
A W.Oak 12" dia., bears N.70°W., 45 lks. dist.

Survey by Glen McChesney - For: Weyerhaeuser Co. - 1958-59 - C.S. File 53/1-39

Post not found.
No evidence of 7" Fir S.60°W., 16 lks.
No evidence of 12" W.Oak, N.70°W., 45 lks.
Found - 8" Fir N.11°E., 71 lks., rotted remains of a Fir stump.
20" Fir S.62°E., 120 lks., rotted remains of a Fir stump.
Set Monel Pipe for cor. from rotted stump N.11°E., 71 lks. and from rotted stump S.62°E., 120 lks.
Referenced by Weyerhaeuser method: (Decl. 20°)
12" Fir S.67°E., 6.5 ft.
53" I.Cedar S.6°E., 25.8 ft.
15" Fir S.69°W., 42.2 ft.
11" Fir N.55°W., 12.0 ft.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #398 Surveyed, April/May/ 1958 - (DCSO records Vol. 31 Page(s) 12984-85)

At the Sec. cor., perpetuated by Weyerhaeuser in 1958, monumented with an iron pipe 32" long, 2½" dia. protruding 8" above ground, from which the remaining original bearing trees:
A rotted Fir stump 28" dia., bears N.11°E., 71 lks. dist. with no marks remaining.
A rotted Fir stump 24" dia., bears S.62°E., 120 lks. dist. with scribe mark B visible on rotted face.
and a tree of which I have no record:
A Cedar 56" dia., bears S.50¼°W., 157 lks. dist. with scribe marks CS visible on old open blaze.
(Cont. Next Page)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and trees marked in 1958 by Weyerhaeuser:

A Fir 14" dia., bears S.65½°E., 10 lks. dist. mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc mkd. Reg. Engineer No. 2149.

A Cedar 53" dia., bears S.4¼°E., 39 lks. dist. mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc mkd. Reg. Engineer No. 2149.

A Fir 15" dia., bears S.70 3/4°W., 64 lks. dist. mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc mkd. Reg. Engineer No. 2149.

A Fir 11" dia., bears N.54°W., 18½ lks. dist. mkd. with a nail stamped W on head and driven through the center of a 3" bronze disc mkd. Reg. Engineer No. 2149.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 21	S R 4 W
S 35	S 36
S 2	S 1
T 22	S
1958	

from which

A Fir 12" dia., bears N.79 3/4°E., 112 lks. dist. mkd. T21S R4W S36 BT.

A Fir 16" dia., bears S.74¼°E., 68 lks. dist. mkd. T22S R4W S1 BT.

A Cedar 11" dia., bears S.80°W., 58½ lks. dist. mkd. T22S R4W S2 BT.

A Fir 12" dia., bears N.27°W., 43 lks. dist. mkd. T21S R4W S35 BT.

Reset Iron pipe alongside the iron post.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 18, 1991 - C.S. File 64/21-6

Corner Report Only

Found - 3¼" dia. BLM brass cap on a 2½" O.D. iron pipe protruding 7" above ground. (1958)

8" now rotted D.Fir stump of indeterminate size, no marks visible, bears N.11°E., 46.9 ft. (agrees w/rec.) Orig. BT.

20" now 18" dia. 2½ ft. high rotted D.Fir stump, no marks visible bears S.62°E., 79.2 ft. (agrees w/rec) Orig. BT.

56" I.Cedar BT noted as "not of record" in 1958 BLM survey, is gone. (Road construction)

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

29" dia. D.Fir with a fully healed double blaze, and a "W" nail driven through the center of a 3" dia. bronze disk marked "Reg. Engineer No. 2149" bears S.65½°E., 6.6 ft. (agrees with 1958 BLM record) Wey. BT

60" dia. 25 ft. high I.Cedar snag bears S.7°E., 29.5 ft. (Rec. S.4½°E., 25.7 ft. 1958 BLM) (No "W" nail found) Wey. Co. BT.

32" dia. D.Fir with a fully healed single blaze and a "W" nail driven through the center of a 3" dia. bronze disk marked "Reg Engineer No. 2149" bears S.69°W., 42.2 ft. (agrees with record) Wey. Co. BT.

26" dia. D.Fir with a fully healed single blaze and a "W" nail driven through the center of a 3" dia. bronze disk marked "Reg. Engineer No. 2149" bears N.54°W., 12.2 ft. (agrees with 1958 BLM) Wey. Co.

12" now 31" dia. D.Fir with a fully healed single blaze, bears N.77½°E., 73.9 ft. (Rec. N.79 3/4°E., 73.9 ft.) 1958 BLM

16" now 24" dia. tipped out D.Fir with a fully healed single blaze, root hole bears S.74¼°E., 44.9 ft. (agrees w/rec) 1958 BLM

7" now 12" dia. 7 ft. high Cedar snag with an open blaze, scribing visible "T22S R4W" bears N.79°W., 38.6 ft. (Rec. N.80°W., 38.6 ft.) 1958 BLM

12" Fir bearing N.27°W., in 1958 BLM is gone.

See Lane County Surveyor's Office for the most current information