

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Jesse Applegate DLC #38

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Set Stone post 6 x 9 x 12" for NW cor., from which  
An Oak 20" dia., bears N.5°W., 72 lks.  
An Oak 18" dia., bears S.87°E., 105 lks.

A. R. Evans and Milo Godfrey - April 6, 1948 - C.S. File  
39/167 and M 16-67

-----  
Found - Rock corner, identified from old Oak witness tree,  
N.5°W., 72 lks., standing, scribed marks plain.  
Reset corner rock.  
Marked BT:  
16" D.Fir N.44¼°W., 35.5 ft.  
24" D.Fir S.64½°W., 39.7 ft.

Survey by Wilford N. Haines - For: Woolley Logging - Dec.  
1963 - M 27-17

-----  
Found - Old BT, N.5°W., 47.5 ft.  
16" Fir N.44¼°W., 35.5 ft.  
24" Fir S.64½°W., 38.3 ft.  
Rock as mentioned by Evans & Godfrey, is gone.  
Set 1" x 1" x 36" T Iron flush with ground.

Fd. OK, DCSO, B.Rogers, March 15, 1965, C.S. File 53/101

Survey by Bruce Shaner - For: Woolley Enterprises, Inc. -  
Nov. 1980 - RM 3-60

-----  
Found - Haines T Iron.  
24" D.Fir, stump, BT, bears S.64½°W., 39.4 ft. (Rec.  
38.3 ft.)  
18" D.Fir, stump, bears N.44½°W., 35.5 ft.  
24" D.Fir, two stumps, bears N.5°W., 45.3 ft. (Rec.  
47.5 ft., orig. BT)  
Set Brass Cap. Reset Haines' T-Iron alongside brass cap.

Fd. B.C., Feb. 1991, Land Partition 1991-0007

continued next page

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Jesse Applegate DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 11/7/2001 - C.S. File 66/29-23

Found - 1980 2½" O.D. brass cap/iron pipe, protrudes 2" out  
of ground marked T22S R5W W.M.

/ / DLC 38

RLS 430 1980

1963 Haines "T" iron along North edge of BC/IP  
protrudes 2" out of ground. Corner is at a 3-way  
fence corner with lines running W'ly, SW'ly &  
NE'ly.

Note: 20" Oak now root hole bears N.5°W., 47.5 ft. (OBT)  
24" double trunked D.Fir stump in 1980 renewal is  
not orig. NW BT.

16" now 18" dia., 6 ft. high D.Fir stump with a  
fully healed double blaze bears N.44¼°W., 35.5  
ft. (1948)

24" now 25" dia., 5½ ft. high D.Fir stump with a  
fully healed blaze, bears S.67½°W., 39.4 ft.  
(Rec. S.64½°W., 39.4 ft.) (1948)

New - 22" dia., W.Oak double blazed & scribed "NW DLC 38  
CS BT" bears N.52½°W., 33.2 ft.

22" dia., W.Oak double blazed & scribed "NW DLC 38  
CS BT" bears N.4½°E., 89.8 ft.

15" dia., D.Fir double blazed & scribed "NW DLC 38  
CS BT" bears N.38½°E., 136.3 ft.

Compass decl. 17½°E.