

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; and 25 of T22-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1383)

Set ¼ sec. post, from which
A W.Oak 12" dia., bears S.9°E., 71 lks. dist.
A W.Oak 15" dia., bears S.82°W., 258 lks. dist.

Survey by James Branch - For: U.S. National Bank - Nov. 25, 1992 - C.S. File 63/149-1H and M 116-29

Set 5/8" x 30" rebar with yellow plastic cap mkd. "Branch Eng. LS 1138"., from which
34" Cedar bears S.56°W., 204.2 ft. scribed "¼ S30 BT"
9" Oak bears N.82°E., 154.0 ft. scribed "¼ S30 BT"
10" Oak bears N.84°E., 177.5 ft.
22" Ash bears N.86°W., 241.4 ft.

Fd. OK - Ken Hoffine - July 1995 - C.S. 65/8-2

DCSO-GIS Corner visitation - 11/18/2005 - Typed: 1/13/2011 - C.S. File 67/33-1

Monument - rebar, 5/8" IR w/ypc Comment - ok; 4 live BTs

Fd. OK, Oct. 2007, R Betz, M154-40 **(replaces M116-29 & C.S. FILE 63/149-1H)**