

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; and 12, T22-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1385)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Laurel 24" dia., bears S.39°E., 100 lks. dist. A Fir 20" dia., bears S.83°W., 22 lks. dist.</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow - For: W.E. Clevenger - June 19, 1959 - C.S. File 49/158 and M 15-18</p> <p>-----</p> <p>Found - 3/4" Iron pipe at corner. (No record found for this I.P. - VL 3/9/95) Orig. 20" now 48" Fir stump S.83°W., 14.5 ft. This BT windblown and stump section now downhill about 50 ft., shows good old scars. Now in such position, I cannot open. W. Haines states this BT showed good scribe marks several years ago. Also fine remains of Laurel that may have been original SE BT.</p> <p>New BTs -12" Maple bears S.83°E., 46.0 ft. scribed ¼ S7 CSBT 72" R.Fir bears S.3°E., scribed in wood "BT", scribed in bark "¼ S7". (Dist not given in notes, per J.Crawford 3/9/95 - VL)</p>
<p>Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V.Tracy and Clete Putnam, crew - Oct/Nov. 1961 - C.S. File 49/143-91</p> <p>-----</p> <p>Found - 3/4" I.Pipe at corner as called for in 1959. 12" Maple S.83°E., 46.0 ft. The 72" Fir S.3°E., has blown down.</p> <p>New BT - 32" Fir, North, 52.8 ft. mkd: ¼ S12 CS BT.</p>
<p>Fd. Ok by H.Christensen, Jan. 1995 - M 123-34 Fd. OK by J. Branch, Feb. 1999 - M129-33</p>
<p>BLM Dependent resurvey by A. Bert Skeesick & Timothy J. Moore, Cadastral Surveyors & Robert H. Browning, Surveying Technician under Group No. 2133 surveyed April/May 2006 - (DCSO records Vol. 55 Page(s) 21718)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., perpetuated by Byron, in 1959; subsequently perpetuated by Godfrey, in 1961, monumented with an iron pipe, ¾" dia., firmly set, projecting 3" above ground, from which the remains of an original bearing tree</p> <p style="text-align: center;">continued next page</p>

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; and 12, T22-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole, bears S.83°W., 14.5 ft., with corresponding fallen fir trunk, 31" dia., lying 50 ft. downhill, no marks visible.
and a bearing tree mkd. by Byron
A maple, 14" dia., bears S.84½°E., 45.2 ft., with a healed blaze.
and the remains of a bearing tree mkd. by Godfrey
A shattered fir snag, 38" dia., bears North, 53.1 ft., with fragmentary scribe marks visible on an open blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, over the existing iron pipe, with brass cap mkd.
T22S
R6W R5W
S 12|S 7
¼
2006
from which a new bearing tree
A fir, 13" dia., bears N.12½°W., 7.2 ft., mkd. ¼ S12 BT.
Bury a magnet in a white plastic case at the base of the stainless steel post.