

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias	Description

Original GLO Survey - Harvey Gordon & Charles Gardner ,
Deputy Surveyors - 2/17/1855 - Contract #52 - (DCSO records
Vol. 4 Page(s) 1416)

Set ¼ sec. post; from which
A Laurel, 8" dia., bears N.8½°W., 111 lks.
A Fir, 18" dia., bears S.7½°E., 101 lks.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone
and Stoffel, crew - April 2, 1965 - C.S. File 53/101-16

Corner not found.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flaue
5/31/95 - C.S. 64/63-11

Found - 18" now 36" dia., 4' D.Fir stump, with a
previously opened blaze, scribing visible "4S",
looks to have a fully healed lower
blaze, bears S.7½°E., 66.7' (orig rec.).
Set - 2 3/8" Dia. DCSO Brass cap on a 1 3/8" O.D. by
32" long. Iron pipe is set at record bearing and
distance from remaining OBT. BC/IP protrudes 6"
above ground.
8" dia. Maple, in a cluster of maples is double
blazed and scribed "¼ S7 CS BT" on southwest
trunk of middle four trunked group, bears
N.74¼°E., 10.7' to center of scribed trunk.
9" dia. D.Fir, double blazed and scribed "¼ S7 CS
BT", bears N.7½°W., 56'.
3" dia. D.Fir, double blazed and scribed "X BT",
bears S.14°W., 59.7'.
9" dia. D.Fir, double blazed and scribed "¼ S18
CS BT", bears S.53½°E., 70.9'.
Harvey Christian RLS#2603 fd orig. BT recently and informed
DSCO of it's location. Corner lies on steep easterly slope.

Found OK by C. Sweeden, May 1998 - P. Plat 1998-0049

DCSO-GIS Corner visitation - 11/2/2005 - Typed: 1/13/2011 -
C.S. File 67/33-1

Monument - 1¼ IP W/BC Comment - OK

continued next page

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by A. Bert Skeesick & Timothy J. Moore, Cadastral Surveyors, and Robert H. Browning, Surveying Tech., under Group No. 2133 - Surveyed April/May 2006 - (DCSO records Vol. 55 Pages 21709

The ¼ sec. cor. of secs. 7 and 18, perpetuated by the Douglas County Surveyor's Office, in 1995, monumented with an iron post, 1 ¼" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd from which the remains of an original bearing tree

A sawed fir stump, 32" dia., bears S.7½°E., 66.7 ft., with fragmentary scribe marks visible on an open blaze. and BTs mkd. by the County Surveyor's Office in 1995

A maple, 9" dia., bears N.73¼°E., 10.7 ft., with a healed blaze.

A fir, 18" dia., bears S.53¾°E., 71.0 ft., with a healed blaze.

A fir, 10" dia., bears S. 13½°W., 59.5 ft., with a healed blaze.

A fir, 20" dia., bears N.6¾°W., 56.0 ft., with a healed double blaze.