

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1412)

Set ¼ sec. post, from which
A W.Oak 12" dia., bears N.54°E., 182 lks. dist.
Erected stone mound as per instructions.

O.F. Thiel - For: L.M. Wilcox, etal - March 1911 - Field Book 115 Page 15

At ¼ cor. bet. 30 and 29, marked new bearing trees. Old one cut down.

Wilford N. Haines - Oct. 1964 - C.S. File 51/305

Found - 12" Oak N.54°E., 186 lks., now 24" stump.
Scribed stake in mound of stone.
There is a 28" B.Oak S.38°E., 9.6 ft. and W.Oak 20", N.51°W., 74.2 ft. Looks like they may have been faced for BTs. Did not open either tree.
Set 1" x 1" x 36" T-Iron by stake.
Scribed -8" Fir N.85°W., 53.6 ft.
9" Fir N.9°E., 4.0 ft.

Fd. T-iron, April 1994, H. Pieske, M 120-4

David Edwards - Crew: Brant Miller & Eric Springle - Feb. 13, 2026 - C.S. File 65/116-20

Found - T-Iron in poor condition.
All previous BTs are gone except Haines's, which are stumps.
New - Replaced the T-Iron with a 5/8"x30" steel rebar with plastic cap mkd. "D.A. EDWARDS - L.S. 2339"
A 17" dia. Fir scribed "1/4 S29 BT" bears S.46°E., 68.0 ft.
A 12" dia. Fir scribed "¼ S30 BT" bears S.25°W., 46.6 ft.
5.5 ft steel Posts are set 2 ft East and 3 ft West.
Declination 15° East.