

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 4 Page(s) 1413)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears N.52°E., 135 lks. dist.  
A Fir 24" dia., bears S.70°E., 143 lks. dist.  
No tree accessible West of line.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; A. Bilow - June 20, 1958 - C.S. File 49/59-27

-----  
Found - Orig. 24" now 42" Fir stump S.70°E., 94.4 ft. Butt section of log on ground. I open old scar and find good scribing "¼S".  
Also find rotted stump that checks bearing and distance for orig. NE BT.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 5 W  
¼ S19 | S20  
1958  
New BTs -18" Maple bears N.68½°E., 64.0 ft. scribed ¼ S20 CS BT.  
24" R.Fir bears N.44°W., 59.5 ft. scribed ¼ S19 CSBT  
Sketch in C.S. file for exact location of ¼ corner.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Feb. 1965 - C.S. File 53/101-30

-----  
Found - 18" Maple N.68½°E., 64.0 ft., scribing visible.  
24" R.Fir, now snag, N.44°W., 59.5 ft.  
DCS0 brass cap at corner.  
New BT - 21" D.Fir S.19°W., 93.5 ft. mkd. ¼ S19 CS BT.

Survey by Robert Dean, L.S. #1808 - Feb. 1988 - C.S. File 63/69-20

-----  
Found - 1958 Co. brass cap leaning North. I RESET to vertical position.  
A dead 20" Maple, healed scars, bears N.68°30'E., 64.2 ft. (Rec. N.68½°E., 64.0 ft.)  
A 48" double Fir sawed stump, bears S.71°15'E., 94.6 ft. (Rec. S.70°E., 94.38 ft. per orig. rec.)  
A 28" sawed Fir stump, healed low scar, bears S.19°34'W., 92.2 ft. (Rec. S.19°W., 93.5 ft.)  
22" Fir snag, scribing visible, bears N.44°40'W., 59.1 ft. (Rec. N.44°W., 59.5 ft.)

(Cont. Next Page)

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -10" D.Fir scribed "¼ S20 BT" and 3/4" brass disc "RLS 1808" nailed low to face bears S.45°20'E., 25.3 ft. to center.  
15" D.Fir "¼ S19 BT" and 3/4" brass disc "RLS 1808" nailed low to face, bears S.56°24'W., 24.5 ft. to center.  
Bearings are turned from traverse with theodolite on solar basis. Distances are horizontal to center of root crown.

Found OK by K. Hoffine, April 2004 - M144-38  
Fd. Ok by D. Edwards - 11/2005 - M149-22  
Fd. Ok by D. Edwards - 1/2007 - M152-16

Ken Hoffine - For: Lone Rock - Sept. 2018 - C.S. 65/101-60  
-----  
Found - 1958 County BCIP as per CS 49/59  
24" D.Fir bears S.45°20'E., 25.3 ft. as per CS 63/69  
healed face and tag.  
Down 24" D.Fir bears S.56°24'W., 24.5 ft. as per CS 63/69.  
New BT - 18" D.Fir bears N.61°W., 22.6 ft. we scribe ¼ S19 BT and tag tree  
Note - In the course of visiting the quarter corner between sections 19 & 20 we find only one standing BT with the BT at record bearing of S.56°W., having been uprooted and now laying along side corner. There is a fence corner approx. 13 ft North of corner. Fence lines run North and East from fence corner. There is an old U-Post along side of corner monument and a newer U-Post approx. two feet west of corner monument.  
Rec. bearing from CS File 63/69 hand compass.