

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1413)</p> <p>-----</p> <p>Set post cor. of secs. 17, 18, 19, and 20 Raised stone, mounds as per instructions.</p>
<p>Wilford N. Haines - Oct. 1964 - C.S. File 51/305</p> <p>-----</p> <p>Found - Mound of stone, one with an "X", from which the ¼ corner for sections 19 and 20 bears S.0°04'W., 2641.0 ft. Set 1" x 1" x 36" T-Iron in mound of stone. Scribed -14" Fir S.69½°W., 338.0 ft.</p>
<p>Fd. OK, Feb. 14, 1988, R.Dean, C.S. File 63/69-19</p>
<p>Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - June 28, 1988 - C.S. File 62/52-1</p> <p>-----</p> <p>Found - Haines T-Iron out of position, loosely set and bent. T-Iron is set upside down with top set 6" below ground. Overall length is 4 ft. T-Iron bears N.11°E., 17.0 ft. from the newly set DCSO BC/IP. Stones are scattered through-out area, no distinct mounding or marks found. 27" dia. 1½ ft. high D.Fir stump, a small portion of lower blaze is left on stump, we open and find partial scribing "1" probably lower portion of a "T", bears S.69½°W., 338.0 ft. A 1¼" O.D. x 32" long DCSO brass cap/iron pipe is set at a position determined at record bearing & distance from Haines renewal BT. Brass cap mkd. "Douglas County Surveyors T22S R5W S18 S17 S19 S20 1988 Office" & protrudes 2" above ground. New BTs -11" dia. W.Oak double blazed and scribed "T22S R5W S19 CS BT" bears S.6¼°W., 235.3 ft. 12" dia. double trunked D.Fir double blazed and scribed on East trunk "T22S R5W S19 CS BT" bears (taken to root crown) S.79°W., 71.7 ft.</p>
<p>Fd Ok by Ken Hoffine, June 1995 - M 119-66 Fd.Ok by C.Sweeden, May 1998 - P.Plat 1998-0049 Fd. Ok by D. Edwards - 11/2005 - M149-22</p>
<p>Ken Hoffine - For: Lone Rock - Sept. 2018 - C.S. 65/101-60</p> <p>-----</p> <p>Found - 1988 County BCIP as per CS file 62/52 (properly mkd) 17" Oak bears S.6¼°W., 235.3 ft. as per CS 62/52 (We did not measure) healed face and county tag. CONT</p>

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 18" D.Fir bears N.61°E., 36.4 ft. we scribe S17 BT and tag tree.
17" D.Fir bears S.88°W., 20.9 ft. We scribe S19 BT and tag tree

Note - In the course of visiting the NW corner of section 20. We find 1988 County BCIP 0.2 ft. above ground level. A North South fence line bears approx. 4 ft east of corner. A Westerly running fence line bears approx. 0.5 feet North of corner. There is a U-Post approx. 1.5 ft south of corner monument and a 4" round treated post of "H" brace bears N.60°W., 1.5 ft.
Declination 16°E