

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1416)

 Set post cor. of secs. 5, 6, 7 and 8, from which
 A B.Oak 18" dia., bears N.30°E., 526 lks. dist.
 A B.Oak 10" dia., bears N.32°W., 248 lks. dist.
 A B.Oak 24" dia., bears S.75°W., 212 lks. dist.
 A B.Oak 30" dia., bears S.77°E., 311 lks. dist.

O.F. Thiel - For: Frank Kent - Oct. 1899 - Vol. 2 Page 81 and Field Book 113 Pages 36 & 37 (and F.B. 116 Pg. 51)

 At the NW cor. of Sec. 8, only two bearing trees standing. The SE being dead but standing. S.80°W. tree alive, other trees gone. Established cor. from two trees by setting a Cedar post. (Did not search for NE BT on account of heavy brush and long distance) Marked: A 10" Fir for NW BT, bears N.45°W., 20 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; A. Bilow - Jan. 7, 1958 - C.S. File 49/59-8

 Found - Orig. 24" now 30" B.Oak snag, S.75°W., 139.9 ft. This BT was found and apparently rescribed by Thiel in 1899. I open this BT and find Thiel's "BT 2" under surface. I cut out this BT and find the orig. BT scribing about 5" under our face. All other orig. BTs gone. Also find 3/4" I.R. and old scribed 4" x 4" post at Thiel's corner from which now 28" R.Fir bears N.45°W., 13.2 ft. I open and find good scribing. 3/4" I.R. bears S.20°E., 17.7 ft. I use record distance and bearing from orig. SW BT to establish this section corner as the evidence at this time indicates Thiel was in error in the location of this corner. Set Brass cap at cor. mkd: County Surveyors Office
 T 22 S R 5 W
 S 6 | S 5
 S 7 | S 8
 1958

New BTs -10" R.Fir bears S.77°W., 134.8 ft. scribed T22S R5W S7 CS BT.
 14" R.Fir bears N.58°W., 118.8 ft. scribed T22S R5W S6 CS BT.
 8" R.Fir bears N.3°E., 139.4 ft. scribed T22S R5W S5 CS BT.
 40" B.Oak bears S.4½°E., 168.2 ft. scribed T22S R5W S8 CS BT.
 continued next page

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK, Feb. 1992, D.Peel, M 114-60
Fd. Ok, H.Christensen, Jan. 1995, M 123-34
Found OK by L. Roberts, July 2000 - 2000-0051 A&B

BLM Dependent resurvey by A. Bert Skeesick & Timothy J. Moore, Cadastral Surveyors & Robert H. Browning, Surveying Technician under Group No. 2133 surveyed April/May 2006 - (DCS0 records Vol. 55 Page(s) 21712-3)

The cor. of secs. 5, 6, 7, and 8, perpetuated by Byron, in 1958, from original evidence no longer in existence, and is accepted as the corner, monumented with an iron post, 1¼" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd.

- from which the remains of bearing trees mkd. by Byron
- A sawed fir stump, 18" dia., bears N.2¼°E., 139.1 ft., with a healed blaze.
 - A sawed fir stump, 27" dia., bears S.76½°W., 133.7 ft., with a healed double blaze.
 - A sawed fir stump, 19" dia., bears N.59½°W., 119.5 ft., with a healed blaze.

and new accessories

- A reinforcing bar, 30" long, 5/8" dia., driven 29" in the ground for a reference monument, bears S.65°24'E., 7.9 ft., with aluminum cap mkd. RM T22S R5W S8 7.9 FT TO COR 2006 and an arrow pointing to the corner.
- A reinforcing bar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears S.9°28'W., 8.0 ft., with aluminum cap mkd. RM T22S R5W S7 8.0 FT TO COR 2006 and an arrow pointing to the corner.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 5, 6, 7 and 8, as determined by direct occupation with dual frequency carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Stations (CORS) "CAPE BLANCO CORS ARP" and "DODSON BUTTE CORS ARP", is as follows:

Latitude: 43°40'42.779"N. Longitude: 123°19'39.442"W.
From the corner, a point erroneously positioned as the original cor. of secs. 5, 6, 7, and 8, by Oscar F. Thiel, County Surveyor, in 1899, perpetuated by person(s) unknown with a reinforcing bar, 3/4" dia., firmly set, projecting 2" above ground, bears S.20°14'15"E., 17.62 ft. This point is not properly positioned and is not utilized in this survey.

DCS0-GIS Corner visitation - 10/25/2005 - Typed: 1/13/2011 - C.S. File 67/33-1

Monument - 1¼" IP w/BC Comment - Stumps only; no trees near.

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Fd. BC per record 8/2022 - M Heimburger 2022-0039B