

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2338)

 Set post, cor. to secs. 5 and 6, from which
 A Laurel 8" dia., bears S.3°W., 46 lks.
 A Y.Oak 7" dia., bears S.32½°E., 61 lks.


Survey by Wilford N. Haines - For: Yoncalla Lumber Co. - June 1960 - M 19-6

 Set 1" x 1" x 36" T iron.
 Scribed -8" Fir S.01°E., 26.2 ft.
 6" Fir S.06°W., 27.5 ft.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1119, surveyed Oct. 1982/Feb. 1984 (DCSO records Vol. 46 Page(s) 17670 and Page 17671)

 Point for the standard cor. of secs. 5 and 6, at proportionate distance based on the 1855 Gordon and Gardner resurvey; there is no remaining evidence of the original corner.

Set an Alum. post, 28" long, 2½" dia., 25" in the ground, with alum. cap mkd:



from which

A Fir 18" dia., bears S.7½°E., 67 lks. dist., mkd. T23S R5W S5 SC BT.

A Fir 14" dia., bears S.11°W., 57 lks. dist., mkd. T23S R5W S6 SC BT.

From this same point, an original line tree, bears S.89°59'W., 32.80 chs. dist., an Oak, 37" dia., mkd. with 2 notches on E. and W. faces, from which bearing trees mkd. by person(s) unknown:

A Fir 8" dia., bears S.81½°E., 74 lks. dist., with scribe marks X BT visible on open blaze.

An Oak 11" dia., bears N.35°W., 46½ lks. dist., with scribe marks X BT visible on open blaze.

From this same point, a point established and recorded by Haines in 1960, bears N.45°51'W., 0.047 chs. dist., monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 9" above ground, (Cont. Next Page)

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 206100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 and 6 only, T23-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which a bearing tree mkd. by Haines
A Fir 17" dia., bears S.1°E., 40 lks. dist., with healed
blaze.

Survey by Ken Hoffine - For: Lone Rock Timber Co. - May 1990
C.S. File 63/127-11

Found - Corner is a 1982 BLM alum. cap in good condition.
18" D.Fir bears S.7½°E., 44.2 ft. BLM BT tag
16" D.Fir bears S.11°W., 33.7 ft. BLM BT tag
20" D.Fir bears South 17.3 ft. BT tag, no record.
Metal fence post, 1.5 ft. West, No record.
Haines T iron 1.8 ft. West.
Painted faces and wrote BT on tree trunks of BTs with
fluorescent orange paint. Corner lies on steep West slope
approx. 100 ft. East of creek flowing North.