

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 244100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 5 only, T23-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 6
Page(s) 2337-38)

Set ¼ sec. post, from which
A Y.Oak 13" dia., bears S.58°E., 143 lks.
A Fir 10" dia., bears S.28°W., 204 lks.

Survey by Wilford N. Haines - For: Yoncall Lumber Co. - June
1960 - M 19-6

Found - Orig. 10" Fir S.28°W., 201 lks., now 36".
Set 1" x 1" x 36" T Iron.
Scribed -16" Fir S.32°W., 34.9 ft.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under
Group #1119, surveyed Oct. 1982/Feb. 1984 (DCSO records Vol.
46 Page(s) 17669)

The standard ¼ sec. cor. of sec. 5, perpetuated and recorded
by Haines in 1960, monumented with a "T" shaped iron rod, 1"
dia., firmly set, projecting 4" above ground, with steel
washer, 1" dia., mkd. Wilford N. Haines 239 Survey Point
Drain, Ore., from which the remaining original bearing tree
A Fir 45" dia., bears S.28°W., 204 lks. dist., with scribe
marks 4S visible on opened blaze.
and a bearing tree mkd. by Haines
A Fir 24" dia., bears S.30°W., 53 lks. dist., with scribe
marks ¼ S5 BT visible on bark blaze.

At the corner point
Set an aluminum post, 28" long, 2½" dia., 24" in the ground,
with alum. cap mkd:

1/4 S 5
T 23 S R 5 W
S C
1982

from which a new bearing tree
A Fir 8" dia., bears S.52½°E., 75 lks. dist., mkd. ¼ S5 SC
BT.
Deposit iron rod alongside iron post.

Fd. OK, Feb. 1994, K. Hoffine, M 118-66

DCSO-GIS Corner visitation - 11/30/2005 - Typed: 1/13/2011 -
C.S. File 67/33-1

Monument - "T"-iron Comment - OK, 3 live BTs