

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 4 Page(s) 1404)

Set post cor. of secs. 28, 29, 32 and 33, from which
A Fir 18" dia., bears N.71°E., 63 lks. dist.
A Laurel 18" dia., bears S.18½°E., 114 lks. dist.
A Fir 3" dia., bears S.66°W., 72 lks. dist.
Built mound of stone.

0. F. Thiel - For: Jasper Fegle - Nov. 8, 1900 - Field Book 113 Page 94

Two old bearing trees standing.
Set stone in mound of stone.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; A. Bilow - Jan. 21, 1958 - C.S. File 49/59-4

Found - Orig. 18" now 36" rotted stump N.71°E., 41.6 ft.
This BT opened years ago, now has small section of orig. face in place with good scribing "S28 22".
Also find 30" Fir that checks record dist. and brg. for orig. 3" Fir, S.66°W., 27.5 ft. I do not open.
At corner, I find mound of stone and 12" x 12" x 12" stone with chiseled +.

Set Brass cap at cor. and alongside mound of stone mkd:
County Surveyors Office

T 22 S R 5 W
S 29 | S 28
S 32 | S 33
1958

New BTs -24" R.Fir bears S.86°W., 18.8 ft. scribed S33 T22S R5W CS BT.
7" R.Fir bears N.32½°E., 14.3 ft. scribed S28 T22S R5W CS BT.
8" W.Fir bears N.40½°W., 51.5 ft. scribed S29 T22S R5W CS BT.
33" R.Fir bears South, 29.4 ft. scribed S32 T22S R5W CS BT.

Cor. Fd. OK, DCS0, B.Rogers, MARCH 1965, C.S. File 54/10-1A

Fd. B.C., Dec. 1980, E. Bloom, M 79-64

(Cont. Next Page)

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1119, surveyed Oct. 1982/Feb. 1984 (DCS0 records Vol. 46 Page(s) 17682-83)

The sec. cor., perpetuated and recorded by Byron in 1958, monumented with an iron post 1¼" dia., firmly set, projecting 14" above ground, with 1958 brass cap.

from which the remains of the original bearing trees

A sawed Fir stump 36" dia., bears N.71°E., 63 lks. dist., with fragmentary scribe marks visible on opened blaze.

A Fir 42" dia., bears S.66°W., 68 lks. dist., no marks visible. (Record, 72 lks.)

and bearing trees mkd. by Byron

A Fir 13" dia., bears N.32°E., 22 lks. dist., with healed double blaze.

A Fir 33" dia., bears S.86½°E., 28 lks. dist., with healed double blaze.

A Fir 37" dia., bears S.3 3/4°E., 44 lks. dist., with healed double blaze.

A Fir 19" dia., bears N.40½°W., 78 lks. dist., with healed double blaze.

FD. Ok by Kris DeGroot - July 2007 - M153-57