

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1405)

Set post cor. of secs. 20, 21, 28 and 29, from which
A W.Oak 20" dia., bears N.73°W., 287 lks. dist.
A B.Oak 30" dia., bears S.35°W., 418 lks. dist.
A W.Oak 18" dia., bears S.5°E., & 7.22 chs.
No tree convenient in sec. 21.

O.F. Thiel - Present: Lee Barker and John Fegles - March 1900
Vol. 2 Page 88; Vol. 2 Page 261 and Field Book 113 Page 71

Set a stone 24 x 18 x 12, from which
A W.Oak 8" dia., bears S.86°E., 248 lks. dist.
A W.Oak 6" dia., bears S.41°W., 83 lks. dist.
A W.Oak 6" dia., bears N.52½°W., 90 lks. dist.
A B.Oak 10" dia., bears N.(?)E., 409 lks. dist.
All the original BTs have been cut down, marks were found on three of the remaining stumps, all agreeing in direction and distance with the field notes.

Searched for, not fd, Feb. 1965, DCSO, B.Rogers, C.S. 53/101

Eugene Bloom - For: Fugate & Payne - Dec. 1980 - M 79-64 A&B

Set 1" x 36" Iron pipe with 2½" brass cap stamped PLS 492 1980, from which
A PK nail in a 5 ft. x 6.5 ft. high boulder bears N.57°35'W., 98.8 ft.
5/8" x 24" Iron rod bears S.68°29'W., 19.65 ft.
5/8" x 24" Iron rod bears N.74°53'E., 25.58 ft.
A 14" Fir bears S.52°E., 316.8 ft. scribed T22S R5W S28.

Ken Hoffine - For: Juniper Properties Limited Partnership LLC - Nov. 2011 - 2012-0002

Found - 2½" Bloom cap as per map map M 79-64
5' x 6.5' boulder bears N.59°22'W., 98.96 ft (record N.57°35'W., 98.8 ft) fd PK nail out of position and put in new PK NAIL.
5/8" iron rod bears S.67°33'W 19.69 ft (record S.68°29'W., 19.65 ft)
5/8" iron rod bears N.73°29'E., 25.53 ft (record N.74°53'E., 25.58 ft)
Set - 5/8"x30" iron rod with yellow plastic cap mkd: LONE ROCK TIMBER PLS 2291 bears S.0°39'31"E., 40.2 ft 0.3 ft below ground in centerline of gravel rd.
continued next page

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Corner lies in second growth fir trees and is north approx. 40 ft from centerline of gravel road.

Ken Hoffine - For: Juniper Properties Limited Partnership LLC
- 9/2014 - M168-44 A&B

Found - 1" iron pipe with 2½" brass cap mkd PLS 492 1980 as per M 79-64A.
PK Nail in 5'x6.5'x4.5' High boulder bears N.57½°W., 98.8' Found as per record.
5/8" iron rod bears S.68½°W., 19.68' (Rec. S.68°29'W., 19.65'). 5/8" iron rod bears N.74¾°E., 25.55' (Rec. N.74°53'E., 25.58').
14" fir found as per record.
5/8" iron rod with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 bears S.1/2°W., 40.22' (Rec. S.0°39'31"E., 40.23').

Corner lies in second growth fir trees approximately 40 ft North of center line of gravel road.