

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1409)

Set ¼ sec. post, from which
A R.Fir 36" dia., bears S.30°E., 71 lks. dist.
A R.Fir 12" dia., bears N.19°W., 62 lks. dist.

O.F. Thiel - For: Chas. Schappers - June 19, 1912 - Field Book 115 Page 65

At the ¼ sec. cor. bet. 4 & 9, Set an Iron rod, 18" x 1¼" for cor. by stump of NW tree and marked:
Fir 8" N.18°E., 24 lks.

O.F. Thiel - For: Floyd O. Craig - Aug. 1927 - Field Book 116 Page 24

Iron bolt in place. NW tree standing.

Survey by Thiel found old stake set for the ¼ corner. Oct. 1948 - Field book 5 Page 45

Wilford N. Haines - March 1955 - M 2-63

Found scribed stake.
Set Angle iron with brass cap inscribed "Survey Point - Wilford N. Haines".

Robert Dean - For: Alfred Gurney - Oct. 1983 - M 95-64 A&B

Corner Report Only
Found - 1¼" x 24" iron bar 1 ft. South of old fence. (See Plat of Co. Rd. #68 Sheet 1 June 1935)
A ¾" x 1" T-Iron per survey M 11-68 bears N.75°37'W., 0.50 ft.
A depression bears S.28°38'E., 48.7 ft. (Rec. S.30°E., 46.8 ft.)

Found OK by D. Baker, Feb. 1996 - M124-13
Fd. OK, Jan. 2001, Les Roberts, M 136-51

DCSO-GIS Corner visitation - 10/20/2005 - Typed: 1/18/2011 - C.S. File 67/33-1

Monument - 1½" dia., IR W/T-iron near Comment - NO BTs

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Garrett McGraw - 4/4/2011 - C.S. File 67/33-27

Found - A 1¼" dia., iron rod firmly set and protruding 1" above ground; from which a 1955 renewal monument bears S.83°W., 0.5 ft. (1983 corner report rec. N.75°37'W., 0.50 ft.) 1912

The 1955 monument is a 1" dia., brass washer mkd. "WILFORD N. HAINES 239 SURVEY DRAIN, ORE" ON ¾"x1" "T" iron firmly set and protruding 9" above ground.

Possible evidence of one orig. BT: A R.Fir 36" now a reasonably dist. root-hole; bears S.30°E., 47.5 ft. (as per rec.) No evidence of NW BT remains. No renewal BT evidence is found.

New - A 14" DBH madrone scribed "¼ S4 CS" "BT" on a double blaze; bears N.7½°E., 34.5 ft.

A 19" DBH D.Fir scribed "¼ S4 CS" "BT" on a double blaze; bears N.47°E., 42.2 ft.

A 11" DBH W.Oak scribed "¼ S9 CS" "BT" on a double blaze; bears S.54½°E., 11.5 ft.

No suitable tree in SW quadrant.

A metal witness sign & post bears North 0.4 ft.

Note - Monument lies on gentle west slope at north edge of large clear cut.

15¾°E Decl.