

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1400)</p> <p>-----</p> <p>Set post cor. of secs. 21, 22, 27, &amp; 28 Deposited charred stake. Raised mound with trench &amp; pits as per instructions.</p>
<p>Ken Hoffine - For: Lone Rock Timber Co. - 8/2001 - M 137-17</p> <p>-----</p> <p>Corner position computed by double proportion (as per BLM) Set 2 reference monuments: Set - 5/8" Iron rod with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 23" D.Fir bears N.20½°E 54.3 ft. We scribed "BT" &amp; tag. 21" D.Fir bears S.32¼°E. 29.3 ft. We scribed "BT" &amp; tag The calculated position for the NW corner of sec. 27 bears N.89°22'33"W., 109.514 ft. Note- Corner lies on steep West slope approx. 150 ft. above pasture in mixed conifer's &amp; hardwoods.</p> <p>-----</p> <p>Set - 5/8" Iron rod with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 9" D.Fir bears S.46¾°E., 17.0 ft. We scribe "BT" &amp; tag. 12" D.Fir bears S.27¾°W. 23.6 ft. We scribe "BT" &amp; tag. The calculated position for the NW corner of sec.27 bears N.0°15'25"E., 185.482 ft. Note- Corner lies on very steep West slope in mixed hardwoods &amp; young conifer reprod.</p>
<p>FD. Ok by K. Hoffine 4/2008 - M155-54</p>
<p>Ken Hoffine - For: Juniper Properties Limited Partnership LLC - 9/2014 - M168-44 A&amp;B</p> <p>-----</p> <p>Computed corner position as per M 137-17. Found - 5/8" iron rod with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 bears S.1/2°W 185.49' (Rec. S.0°15'25"W. 185.48'). 5/8" iron rod with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 bears S.89¼°E., 109.51' (Rec S.89°22'33"E., 109.51'). Computed corner position from record distances of found reference monuments.</p>
<p>1</p>