TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1401)

Set post cor. of secs. 15, 16, 21 and 22, from which
A B.Oak 15" dia., bears N.57°W., 60 lks. dist.
A Laurel 20" dia., bears S.25°W., 59 lks. dist.
A B.Oak 18" dia., bears S.50°E., 7 lks. dist.
A Laurel 3" dia., bears N.30°E., 50 lks. dist.

Cor. not found, DCSO, B. Rogers, Feb. 16, 1965, C.S. File 53/101-33

Survey by Donald Peel, LS #752 - For: Weyerhaeuser Company - Jan. 1988 - M 105-54

Set 2" x 42" Iron pipe with brass cap mkd: T22S R5W S16 | S15
PLS 752 S21 | S22
1988

New BTs -10" Oak, East 63.3 ft. scribed T22S R5W S15 BT.
13" Fir, S.12 3/4°E., 240.3 ft. scribed T22S R5W S22 BT.
15" Maple S.13¼°W., 218.2 ft. scribed T22S R5W S21 BT.
12" Oak N.27½°W., 89.4 ft. scribed T22S R5W S16 BT.

Found OK by K. Hoffine, Aug. 2001 - M137-17