

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1402)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.80°E., 33 lks. dist.
A Fir 36" dia., bears S.48°W., 57 lks. dist.

B.H. McGillicuddy - For: Whipple Lumber Co. - April 1952
RM 1-40

Post, Iron pipe.
Orig. Fir 10" S.80°E., 33 lks., now stump 36".
Orig. Fir 36" S.48°W., 57 lks., now 50" tree.

Douglas Co. Surveyors Office - Bruce R. Rogers, Deputy - Stoffel and Stone, crew - Feb. 1965 - C.S. File 53/101-32

Found - Orig. BT, 10" Fir, now stump, S.80°E., 21.8 ft.
Orig. BT, 36" Fir, now stump, S.48°W., 37.6 ft.
4 x 4 scribed post and 1" Iron pipe at corner.
New BTs - 24" W. Fir S.29°E., 21.1 ft. mkd. ¼ S15 CS BT.
22" Cedar N.68°W., 29.5 ft. mkd. ¼ S16 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/23/2001 - C.S. File 66/21-21

Found - 1" I.D. iron pipe, protrudes 29" out of ground at a fence corner. Fence line runs S-N+W. 1952
10" now 34" dia., 1½ ft. high rooted D.Fir stump bears S.80°E., 21.8 ft. (OBT)
36" now 46" dia., 4 ft. high D.Fir stump with a previously opened blaze. No scribing visible, bears S.48°W., 37.6 (OBT)
24" now 30" dia., 3 ft. high, tipped out of ground on face bears S.29°E., 21.1 ft. (1965)
22" now 36" dia., 2 ft. high Cedar stump w/fully healed blaze, bears N.68°W., 29.5 ft. (1965)
New - 9" dia., D.Fir single blazed & scribed "¼ S15 CS BT" bears N.69°E., 12.5 ft.
5" dia., D.Fir double blazed & scribed "¼ S16 CS BT" bears N.59°W., 25.0 ft. to center of scribed trunk tree is pistol butt.
8" dia., D.Fir double blazed & scribed "¼ S1 CS BT" bears S.4°E., 14.4 ft.
14" dia., W.Oak double blazed & scribed "¼ S16 CS BT" bears S.58½°W., 31,4 ft.
Position of FD IP referenced & removed IP is 5 ft. long. continued next page

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" long
iron pipe stamped: DOUGLAS COUNTY SURVEYORS
T22S

R
¼ S 16 | S 15 5
2001 W
OFFICE

protrudes 4" out of ground. 1952 Fd. IP is set
along west edge of BC/IP protrudes 22" out of
ground.
Compass decl. 17 3/4° E