

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1403)

-----  
Set ¼ sec. post, from which  
A Fir 6" dia., bears N.56°W., 25 lks. dist.  
A Laurel 3" dia., bears S.42°E., 15 lks. dist.

B.H. McGillicuddy - For: Whipple Lumber Co. - April 1952  
RM 1-40

-----  
Post and iron pin.  
Orig. BT, 6" Fir, N.56°W., 25 lks., now 30".  
Orig. BT, 3" Laurel S.42°E., 15 lks., stump.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby, Mike Stone, Terry Conell, crew - Aug. 3, 1965 - C.S. File 53/101-45

-----  
Found - 1/2" Iron rod with eye on top as recorded in 1952.  
Orig. 6" now 30" Fir N.56°W., 16.5 ft., find "¼S" scribe and reverse face and scribe where BT would be about 6".  
Other bearing trees now gone.  
New BT - 5" Laurel S.49°E., 10.0 ft. mkd. ¼ S10 CS BT.  
No other trees available.  
Corner lies on steep West slope of hill in dense brush.

Fd. OK, May 1982, W. Haines, M 92-31

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 3, 1988 - C.S. File 62/59-3

-----  
Found - A firmly set 1/2" iron rod with eye on top protrudes 6" above ground, eye bolt leans 6" West of plumb. (Source unknown)  
6" now 30" dia. rotting D.Fir snag with a previously opened blaze, scribing visible "¼ S" bears N.56°W., 16.5 ft. (agrees w/rec) Orig. BT.  
5" now 9" dia. Madrone partially rotted blaze opened and scribing "S10" found., bears S.49°E., 9.2 ft. (Rec. S.49°E., 10.0 ft., dist. is a slope measurement.)  
BRASS CAP NOT SET.  
Corner lies in a steep rocky area with shallow soil.  
New BTs -6" dia., Maple, double blazed and scribed "¼ S9 CS BT", bears S.6°W., 67.6 ft.  
5" dia. Madrone, bark scribed "¼ S10 CS BT", bears N.6°E., 22.2 ft. (Cont. Next Page)

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Bearings and distances of found BTs taken to plumb position  
of eye bolt.  
Corner lies on steep westerly slope.

Fd. OK, Feb. 1991, M 111-54  
Fd. OK, Jan. 2001, Les Roberts, M 136-51  
Fd. Ok, April 2004, by Ron Rice, M144-52