

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1399-1400)

-----  
Set ¼ sec. post. Deposited charred stake, raised mound with trench and pits as per instructions.

Survey by W.S. Barnes - For: Rex Applegate - July 1974 - M 53-74

-----  
Set Brass cap mkd: T22S R5W ¼ S27 S34 P.E. 2128.  
BTs - 18" Oak bears N.43°E., 23.5 ft. scribed ¼ S27 BT.  
9" Oak bears S.20°E., 18.8 ft. scribed ¼ S34 BT.

Found OK by K. Hoffine, Aug. 2001 - M137-17

Ken Hoffine - For: Lone Rock Timber Co. - 4/2008 - M155-54

-----  
Found - Brass cap PE2218 cap 1.0 ft. above ground.  
17" Oak bears S.18¾°E., 18.9 ft. as per M137-17, healed face & tag.  
17" Rotted Oak stump bears N.41¼°E., 23.1 ft. as per M137-17  
New BT - 10" D.Fir bears S.75¾°W., 42.0 ft. We scribe ¼ S34 BT & tag.  
Corner lies on south slope. An old fence line that runs North-South bears East approx. 8 ft.

Robert Cook - For: Cambell-Global - 5/2019 - M175-60

-----  
Found - 2½" brass cap up 12" per M53-75, 6.5 ft west of  
downed N-S 4' wire fence.  
22" Oak S.19°E., 18.9 ft. healed face and tag per M53-75