

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1402)

Set ¼ sec. post, from which
 A W.Oak 10" dia., bears N.73°W., 536 lks. dist.
 A W.Oak 20" dia., bears S.81°W., 71 lks. dist.

Corner not found, 1965, DCSO, B.Rogers, C.S. File 53/101-80

Survey by Donald Peel, L.S. #752 - For: Weyerhaeuser Company - Jan. 1988 - M 105-54

Set 2" x 42" Iron pipe with brass cap mkd: T22S R5W ¼ S15 S22 PLS 752 1988.
New BTs -25" Fir N.27°E., 74.8 ft. scribed ¼ S15 BT.
 34" Oak S.83°E., 142.1 ft. scribed ¼ S22 BT.
Distances are center measure, bearing solar.

Found OK by K. Hoffine, Aug. 2001 - M137-17

DCSO-GIS Corner visitation - 1/12/2006 - Typed: 1/18/2011 - C.S. File 67/33-1

Monument - 2½" BC on IP Comment - 2 love BTs