

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1424)

Set post 4" dia. 4 ft. long with marked stone 12" in ground for ¼ sec. cor. mkd. ¼ S on N. face; from which
A Fir 14" dia., bears S.56°W., 72 lks. dist. mkd. ¼ S BT
A Fir 10" dia., bears N.51½°E., 104 lks. dist. mkd. ¼ S BT

Victor McLind - For: Floyd & Lena Rust - June 1973 - M 48-78

No evidence found of original corner.
Set corner by single proportionate measurement.
Set 1" Iron pipe with brass cap stamped: T22S R5W ¼ S3 S10 RLS 934 1973.
New BTs -26" Madrone bears S.1°W., 13.2 ft. scribed ¼ S10 BT
16" Madrone bears N.33°W., 24.6 ft. scribed ¼ S3 BT

Ronald Geisler, PLS #1988 - For: Champion International Corp. Feb. 1991 - C.S. File 63/113 and M 111-54

Found - 1973 DCSO BC/IP.
26" Madrone bears S.1°W., 13.2 ft.
16" Madrone bears N.34°W., 25.0 ft. (Rec. N.33°W., 24.6 ft.)
New BTs -18" Fir bears N.7°E., 4.9 ft. scribed ¼ S3 BT.
11" Fir bears S.63°E., 34.5 ft. scribed ¼ S10 BT.

Fd. OK, Sept. 1993, D.Baker, M 118-10
Fd. as per record, 3/2019 - M Schulze 2019-0029 A&B