

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 4 Page(s) 1395-96)

-----  
Set ¼ sec. post, from which  
A B.Oak 5" dia., bears N.39°W., 8 lks. dist.  
A B.Oak 3" dia., bears S.6°E., 52 lks. dist.

-----  
O.F. Thiel - For: Chancy Smith - July 10, 1942 - Field Book 117 Page 32

-----  
Stone, 12 x 8 x 5. Marked:  
15" Fir S.10°E., 25½ ft.  
Corner on slope.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S. Bilow - Feb. 24, 1958 - C.S. File 49/59-14

-----  
Found - 12" x 8" x 5" stone with chiseled + on top.  
15" now 24" R.Fir, I open lower scar and find good scribing "BT". Stone and Fir BT from Thiel's Book = 14. (Now F.B. 117 Pg. 32)  
I find base of old Oak stump that checks original dist. & brg. for SE BT.  
I find no trace of orig. NW BT.  
Set brass cap alongside corner stone mkd:  
County Surveyors Office  
T 22 S R 5 W  
¼ S27|S26  
1958

New BT - 10" Fir N.48°W., 24.0 ft. scribed ¼ S27 CS BT.

-----  
Fd. OK, Feb. 1965, DCS0, C.S. File 53/101-86  
Found OK by K. Hoffine, Aug. 2001 - M137-17