

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias <u>043010</u>	Description <u>NE Cor. Lyons DIC #43</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1397)

Set post cor. of secs. 14, 15, 22 and 23, from which
A B.Oak 40" dia., bears N.9°E., 21 lks. dist.
A B.Oak 18" dia., bears S.32°W., 59 lks. dist.
A B.Oak 12" dia., bears S.32°E., 75 lks. dist.
A Fir 20" dia., bears N.27°W., 131 lks. dist.

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy, dated Sept. 1856

Beginning at the NE. cor. which is the NE. corner of Sec. 22.

Cor. Fd. and used by B.H. McGillicuddy, April 1952, RM 1-40

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S. Bilow - Jan. 29, 1958 - C.S. File 49/59-2

Found - Orig. 40" now 52" B.Oak N.9°E., 13.9 ft. I open and find good scribing "2 S".
Rotted base of large Fir stump that checks bearing and distance for orig. NW BT.
1" Angle iron with 1" brass cap mkd. 239 Survey Point.
6" x 2" sandstone 14" above ground alongside angle iron at 4-way fence corner which is at sec. cor.
New BTs -18" R.Fir bears N.68°E., 24.5 ft. S14 T22S R5W CS BT
7" R.Fir bears S.42°E., 17.5 ft. S23 T22S R5W CS BT
14" R.Fir bears N.11°W., 22.9 ft. S15 T22S R5W CS BT
10" R.Fir bears S.16°W., 30.7 ft. S22 T22S R5W CS BT

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 812 Surveyed Aug./Sept. 1973 (DCSO records Vol. 36 Page(s) 15067-68)

The Sec. cor., perpetuated by Byron in 1958, monumented with an iron rebar, 1" dia., firmly set, protruding 6" above ground, from which the remains of the original bearing tree:
A B.Oak 46" dia., bears N.9°E., 21 lks. dist., with scribe marks 2 S visible on opened blaze.
and bearing trees mkd. by Byron:
A Fir 25" dia., bears N.70°E., 37 lks. dist., with healed blaze.
A Fir 12" dia., bears S.38°E., 25 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias 043010 Description NE Cor. Lyons DIC #43

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A Fir 15" dia., bears S.20°W., 46½ lks. dist., with healed blaze.

A Fir 17" dia., bears N.7°W., 35½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S R 5 W

S 15 | S 14

S 22 | S 23

1973

Deposit iron rebar alongside iron post.

Fd. OK, Aug. 1994, D. Baker, M 119-39