

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1422)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. mkd. ¼ S on W. face; from which
A Fir 24" dia., bears S.65°W., 32 lks. dist., mkd. ¼ S BT.
A Fir 24" dia., bears N.50°E., 34 lks. dist., mkd. ¼ S BT.

B.H. McGillicuddy - For: Whipple Lumber Co. - April 1952 - RM 1 - 40

New post and 1" x 5 ft. pipe for corner.
Orig. BTs:
Fir 24" S.65°W., 32 lks, scribed on bark, now 36".
Fir 24" now 40", N.50°E., 34 lks., scribe burned.

Bruce A. Shaner - For: U.S. BLM - Sept. 18, 1972 - M 49-12

Found - 1" I.P. and a 4" x 4" post.
40" orig. D.Fir, face visible, bears N.55½°E., 20.7 ft. (Rec. N.50°E., 22.4 ft.)
36" orig. D.Fir, face visible, bears S.64¼°W., 20.3 ft. (Rec. S.65°W., 21.1 ft.)
Set Brass cap mkd: T22S R5W WM S10 S11 ¼S 1972. Placed iron pipe beside brass cap.

Fd. OK, Feb. 1991, M 111-54