

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 791)

Set post cor. of secs. 2, 3, 34 and 35, from which
A Fir 30" dia., bears S.33°E., 26 lks. dist.
A Dogwood 6" dia., bears S.68°W., 26 lks. dist.
A Fir 14" dia., bears N.54°W., 12 lks. dist.
A Fir 12" dia., bears N.20°E., 17 lks. dist.

Wilford N. Haines - (date ?) - Haines field book, H-114

Orig. 30" Fir stump, S.33°E., 26 lks.
14" Windfall, N.54°W., 12 lks.
Scribed -14" W.Fir N.21°E., 31.3 ft.
28" Fir S.60°E., 7.6 ft.
46" Fir S.22°W., 44.2 ft.

B.H. McGillicuddy - Wit: Roy Doty and Howard Hopkins - July 1953 - C.S. File 41/182

Original BTs:
30" Fir, now stump, S.33°E., 26 lks.
14" Fir N.54°W., 12 lks., windfall.
New BTs -14" W.Fir N.21°E., 31.3 ft. Tp 21S R5W S35 BT.
28" Fir N.21°W., 9 ft. Tp 21S R5W S34 BT.
46" Fir S.22°W., 44.2 ft. Tp 22S R5W S3 BT.
SW BT destroyed.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy - 1965 - C.S. File 53/101-3

Found - Squared stake at corner.
Orig. 30" Fir now stump, S.33°E., 17.2 ft. scribes visible.
Orig. 14" Fir, down, N.54°W., chopped out and found scribe.
14" W.Fir now 19" N.21°E., 31.3 ft. scribe visible.
28" Fir N.21°W., 9.0 ft. scribing visible.
46" Fir S.22°W., 44.2 ft. scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T21S
S 34 | S 35 R5W
S 3 | S 2
T22S
1965

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T21-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Fd. OK, Oct. 1988, D.Wellman, M 107-26 & C.S. File 63/85-4
Fd. OK, Sept. 1993 by D. Baker - M 118-10
Fd OK by T. Rambo, Jan. 2004 - M143-75 Noted: All record BT's are stumps.

Douglas Co. Surveyors Office - Stephen J. Flauser - John Pike
- 5/10/2007 - C.S. File 67/21-36

Found - 2½" dia., brass cap on 1¼" O.D. iron pipe projects 5" above ground. NOTE: Date was NOT stamped on BC Orig. 30" now indeterminate dia., rotting, D.Fir stump, approx. 5 ft. tall orig. scribing intact, bears S.33°E., 17.2 ft. (agrees w/rec.) OBT
19" now 28" dia., x 3 ft. tall rotting D.Fir stump, healed low blaze bears N.21°E., 31.3 ft. (agrees w/rec)
28" now blown down & cut office Fir stump - no position (Rec. N.21°W., 9.0 ft.)
46" now 57"x4 ft tall D.Fir stump, top cut at angle, and capped with galv. roofing, healed blaze visible, bears S.22°W. (No dist meas. due to thick under brush, bearing was noted by pointing compass at L.E.D.)
New - Stamped date "1965" onto brass cap.
Double trunk hemlock, westerly trunk is 8" dia., & scribed "T22S R5W S2 CS BT" bears S.35°E., 16.2 ft. Tree is growing on side of OBT stump
4" dia., D.Fir, double blazed & scribed "X CS" on high blaze & "BT" on low blaze bears S.42¾°W., 15.4 ft.
5" dia., G.Fir, double blazed & scribed "X CS" on high blaze & "BT" on low blaze bears N.51°W., 42.9 ft.
Note - Lies on NE facing slope on West side of steep draw in dense undergrowth & young fir trees.
Compass decl. 16¼°E.

Adam DeGroot - For: Silver Butte Timber Co. - Dec. 2019 -
C.S. File 65/105-2

Found - A 1¼" dia. iron post by DCSO in 1965, firmly set and projecting 8" above ground, with a 2½" brass cap properly mkd from which the 2007 BTs
A 11" Hemlock bears S.34°30'E., 16.5 ft w/scribe marks visible on partially healed dbl blaze {S.35'E., 16.2 ft}
A 9" D.Fir bears S.42°15'W., 15.4 ft w/healed dbl. blaze {S.42¾°W., 15.4 ft}

continued next page

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T21-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 10" G.Fir bears N.51°30'W., 42.7 ft w/healed dbl.
blaze {N.51°W., 42.9 ft}
I did not retie the record stumps