

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1397)

Set 1/4 sec. post, from which
A W.Oak 20" dia., bears N.75 1/4° E., 666 lks. dist.
A W.Oak 12" dia., bears S.63 3/4° E., 552 lks. dist.

B.H. McGillicuddy - For: Whipple Lumber Co. - April 1955 - C.S. File 42/33

Set 1" x 30" Iron pipe half way between section corners in open prairie. No bearing trees.

Search for corners shown as found in C.S. File 42/33, did not substantiate this work. See C.S. File 49/59

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 812 Surveyed Aug./Sept. 1973 (DCSO records Vol. 36 Page(s) 15068)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 5 W

1/4 S 14

S 23

1973

No suitable bearing trees available within limits.

Fd. OK, Feb. 23, 1988, D.Peel, M 105-69

Fd. OK, Sept. 1994, D.Baker, M 119-39