

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1423)

Set post 4" in dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. mkd. 1/4 S on N. face; from which
A Fir 24" dia., bears N.42°E., 31 lks. dist. mkd. 1/4 S BT.
A Fir 12" dia., bears S.22°E., 44 lks. dist. mkd. 1/4 S BT.

B.H. McGillicuddy - For: Whipple Lumber Co. - April 1952 - RM 1-40

Post and rocks in original position.
Original BTs destroyed.

Bruce A. Shaner - For: U.S. BLM - Sept. 18, 1972 - M 49-12

Found - 5" x 5" post scribed "1/4S" on West face.
Mound of stone approx. 1 ft. SE of the post. I found no markings on the stones nor any original BTs. Same as described by McGillicuddy.
Set Brass cap mkd. T22S R5W WM 1/4S S2 S11 1972.
New BTs -15" D.Fir bears N.56°E., 15.5 ft. scribed 1/4 S2 BT.
48" D.Fir bears S.67 1/4°W., 8.3 ft. scribed 1/4 S11 BT.

Fd. ok by Rex Betz - 3/15/1999 - M 131-27

Kristian DeGroot - For: Silver Butte Timber Co. - Jan. 2014 - M167-14

Found - A 1 1/4" iron post by Shaner in 1972 per M49-12, firmly set, projecting 12" above an 18" mound of stone, with a 2 1/2" brass cap (properly) mkd.
From which bearing trees by Shaner in 1972:
A 20" D.Fir stump bears N.53°45'E., 15.4 ft. with no marks visible (N.56°E., 15.5')
A 51" D.Fir bears S.69°15'W., 7.7 ft. with healed single blaze (S.67°15'W., 8.3')
And un-recorded BTs by Dan Baker, PLS 1978 in 2010:
A 6" D.Fir bears N.57°15'E., 13.5 ft. with visible X upper blaze and pitched over lower blaze. (Tag N.61°E., 13.8')
A 11" D.Fir bears S.38°E., 8.6 ft. with pitched over single blaze. (Tag S.35°E., 8.7')
NAD83 CORS96 (EPOCH 2002.00) Geodetic Coordinates
Latitude: 43°40'42.33413"N Longitude: 123°15'28.03798"W