

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1390)

Set post cor. of secs. 25, 26, 35 and 36, from which
A B.Oak 10" dia., bears N.80°E., 44 lks. dist.
A Laurel 14" dia., bears N.50°W., 18 lks. dist.
A Fir 24" dia., bears S.29½°E., 82 lks. dist.
A Fir 15" dia., bears S.17°W., 155 lks. dist.

O.F. Thiel - Sept. 1926 - For: Cochran Bros. - Field Book 116 Page 7

SE bearing tree standing. (Remarked same)
Stump of NE and NW trees found.
Set a Cedar post.

Survey by Wilford N. Haines - For: Woolley Logging Co. - April 1964 - M 27-65

Found - Three original bearing trees.
Set 1" x 1" x 36" T-Iron.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 812 Surveyed Aug./Sept. 1973 (DCSO records Vol. 36 Page(s) 15060)

The Sec. Cor., determined at record bearing and distance from the remains of the original bearing trees:

A Fir 35" dia., bears S.29½°E., 82 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.
A Fir 55" dia., bears S.17°W., 155 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S R 5 W
S 26 | S 25
S 35 | S 36
1973

from which new bearing trees

A Fir 21" dia., bears N.24°E., 81½ lks. dist., mkd. T22S R5W S25 BT.
A Fir 23" dia., bears N.25°W., 45½ lks. dist. mkd. T22S R5W S26 BT.

Fd. OK, Oct. 1992, K. Hoffine, M 116-2

continued next page

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DCSO-GIS Corner visitation - 1/5/2006 - Typed: 1/19/2011 -
C.S. File 67/33-1

Monument - 3" BC

Comment - (needs) rehab