

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1391)

-----  
Set ¼ sec. post, from which  
    A Fir 6" dia., bears N.22°W., 64 lks. dist.  
    A Fir 20" dia., bears N.22°E., 85 lks. dist.

Survey by Wilford N. Haines - For: Woolley Logging Co. - April 1964 - M 27-65

-----  
Found - 20" Fir N.22°E., 85 lks., now 48", good scribe.  
Set 1" x 1" x 36" T-Iron for corner.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 812 Surveyed Aug./Sept. 1973 (DCSO records Vol. 36 Page(s) 15060)

-----  
The ¼ sec. cor., determined at record bearing and distance from the remains of the original bearing tree

    A Fir 48" dia., bears N.22°E., 85 lks. dist., with scribe mark B visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

                                  1/4  
                                  S 26 S 25  
                                  T 22 S R 5 W  
                                  1973

from which a new bearing tree

    A Fir 8" dia., bears S.54°W., 43 lks. dist., mkd. ¼ S26 BT