

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1391)

-
- Set post cor. of secs. 23, 24, 25 and 26, from which
- A Fir 40" dia., bears N.22°W., 29 lks. dist.
 - A Fir 6" dia., bears N.63°E., 35 lks. dist.
 - A Laurel 24" dia., bears S.31°E., 38 lks. dist.
 - A Laurel 15" dia., bears S.37°W., 36 lks. dist.

Survey by Wilford N. Haines - For: Woolley Logging Co. - April 1964 - M 27-65

Found - Stumps of three original bearing trees.
Set 1" x 1" x 36" T-Iron for section corner.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 812 Surveyed Aug./Sept. 1973 (DCSO records Vol. 36 Page(s) 15061)

The Sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A sawed Fir stump 23" dia., bears N.63°E., 35 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.

A sawed Fir stump 50" dia., bears N.22°W., 29 lks. dist., no marks visible on opened and decayed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 5 W
S 23 | S 24
S 26 | S 25
1973

from which new bearing trees

A Fir 6" dia., bears N.63¼°E., 56 lks. dist., mkd. T22S R5W S24 BT.

A Fir 5" dia., bears S.14°E., 21½ lks. dist., mkd. T22S R5W S26 BT.

A Fir 5" dia., bears S.1¼°W., 84½ lks. dist., mkd. T22S R5W S26 BT.

A Fir 41" dia., bears N.35 3/4°W., 32 lks. dist., mkd. T22S R5W S23 BT.

DCSO-GIS Corner visitation - 1/9/2006 - Typed: 1/19/2011 - C.S. File 67/33-1

Monument - 3" BC

Comment - OK; 4 live BTs, stumps.