

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1392)

-
- Set post cor. of secs. 13, 14, 23 and 24, from which
- A Fir 30" dia., bears N.53°W., 22 lks. dist.
 - A Fir 30" dia., bears S.19°W., 82 lks. dist.
 - A Fir 40" dia., bears S.82°E., 48 lks. dist.
 - A Laurel 15" dia., bears N.17°E., 20 lks. dist.

Survey by B.H. McGillicuddy - March 1955 - C.S. File 42/33

Found - Junction of board fence going East on wire fence going North and South.
Evidence of old BTs in NW.; NE.; and SE. quadrants.
Set 3/4" x 24" iron pipe at intersection of fences from North, South and East., from which

- Fir, burned out stub, N.53°W., 14 ft.
- Fir, burned out stub, S.82°E., 33 ft.
- Fir, burned out stub, S.19°W., 53 ft.

F.D. McMichael disposes to say that he has always accepted said fence corner as above mentioned.

Douglas Co. Surveyors Office - Bruce R. Rogers, Deputy - Stofell and Stone, crew - July 1, 1965 - C.S. File 53/101-38

Found - Corner as described by McGillicuddy.
Burnt stumps fit good for bearing and distance and appear to have been about the right size.
3/4" Iron pipe in 4-way fence.
McGillicuddy did not scribe any trees.

New BTs -12" D.Fir S.43°E., 18.0 ft. mkd. T22S R5W S24 CS BT.
10" D.Fir N.32°W., 18.0 ft. mkd. T22S R5W S14 CS BT.
13" D.Fir S.25°W., 33.1 ft. mkd. T22S R5W S23 CS BT.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 812 Surveyed Aug./Sept. 1973 (DCSO records Vol. 36 Page(s) 15064)

The Sec. cor., perpetuated by McGillicuddy, in 1955 from original evidence no longer in existence, subsequently perpetuated by Rogers in 1965, monumented with an iron pipe 1" dia., firmly set, protruding 8" above ground, from which bearing trees mkd. by Rogers:

- A Fir 16" dia., bears S.43°E., 26½ lks. dist. with healed blaze.
- A Fir 17" dia., bears S.25°W., 50 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 15" dia., bears N.33°W., 27 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S R 5 W
S 14 | S 13
S 23 | S 24
1973
from which a new bearing tree
A Fir 10" dia., bears N.62°E., 46½ lks. dist., mkd. T22S R5W S13 BT.
Deposit iron pipe alongside iron post.
Corner is located at the intersection of wire fences extending N., S., E. and W.

Fd. OK, Feb. 23, 1988, D.Peel, M 105-69
Found OK by D.Baker, Feb. 1999 - M129-46